失真計 Distortion Meter — JUNG JIN

DM-2100
失真計
Distortion Meter



* Distortion, Sinad, Frequency, Level Measurement
* Spot signal generator (1kHz/400Hz)
* Spot frequency filer (1kHz/400Hz)
* CCITT filter included
* Big size analogue meter
* Automatic frequency selection
* 4 digits frequency counter
* 3 digits delta dB display

STOCK CODE : 641-541 PRICE : HK$ 7,850.00

信納測量錶 Sinad Meter — JUNG JIN

SM-8100
信納測量錶
Sinad Meter



* With CCITT filter
* Input level bar graph monitor
* Range AUTO/MANUAL selection
* Dot band typed meter
* Measurement maximum 30dB sinad
* 1kHz oscillator output
* Speaker monitor
* Revolutionary designed automatic distortion meter for real time measurement of sinad sensitivity

STOCK CODE : 645-087 PRICE : HK$ 2,800.00

磁場儀 Magnetization Inspection — KANETEC

TM-601
物質磁化檢查器
Natural Magnetization Inspection



* Checking iron-removing magnetic bars in the food processing process
* Measuring residual magnetism of electronic components
* Inspection of mechanical stress in stainless steel products
* Range: 0 to 1500 mT (0 - 15,000 G)
* Resolution: 0.01 mT (0.1 G)
* Power: Battery 1.5V x 4 pieces
* Size: 140H x 64W x 30D mm

STOCK CODE : 646-620 PRICE : HK$ 4,880.00

示波器 Oscilloscope — KENWOOD

KENWOOD CS-5455
50兆赫模擬量示波器
50MHz Analog Oscilloscope



* Channels: 3-Channel 8-Trace Waveform Display
* Maximum Sweep Rate of 5 ns/div (x10 MAG)
* Built in Video Clamp Circuit for Easy Operation
* V Mode Sync for Stable Display of 3 Signals
* Bandwidth : 50MHz

STOCK CODE : 644-516 PRICE : HK$ 7,410.00

KENWOOD VA-2230A
音頻分析儀
Audio Analyzer



* Measurements: frequency, AC/DC level, THD, HD, S/N ratio
* DSP for Measurements Based on FFT Computations
* DDS Signal Generator : 5Hz to 20.09KHz
* GP-IB Provided as Standard
* SINAD Measurement . Two Input/Output Channels

STOCK CODE : 646-494 PRICE : HK$ 40,000.00

空氣流量計 Air flow Tracker — KESTREL

KESTREL 4100
空氣流量計
Pocket Air Flow Tracker



* View data on-screen or upload logger data to PC
* Air flow in cfm, L/s, m³/s, m³/m, m³/h
* Air Velocity in ft/m, mph, m/s, km/h, kts, Beaufort
* Temperature in °F or °C
* Humidity in %
* Additional measurements of dewpoint, wind chill and heat stress index

STOCK CODE : 648-434 PRICE : HK$ 2,800.00

石英測量系統 PI-Network Crystal Measurement System — KH

KH-1120
石英測量系統
Network Crystal Measurement System



* Supports "Direct Impedance Measurement" and "Physical Load Capacitance" methods for FL measurement
* Microsoft Windows 95/98/Me operation
* Full Network Analyser Configuration with built-in Frequency synthesizer and Vector-voltmeter
* Frequency range : 1-120 MHz
* Drive Level : 10nW - 1mW into 25Ω
* Measurement capabilities (more than 48 parameters)

STOCK CODE : 646-014 PRICE : HK$ 5,100.00

KH-1240
石英測量系統
Network Crystal Measurement System



* Supports "Direct Impedance Measurement" and "Physical Load Capacitance" methods for FL measurement
* Microsoft Windows 95/98/Me operation
* Full Network Analyser Configuration with built-in Frequency synthesizer and Vector-voltmeter
* Frequency range : 20 KHz, 400 KHz, 500KHz, 240MHz
* Drive Level : 10nW - 1mW into 25Ω
* Measurement capabilities (more than 48 parameters)

STOCK CODE : 646-015 PRICE : HK$ 38,844.00

石英測量系統 PI-Network Automatic Quartz Crystal Final Sort Measurement System — KH

KH-3020
石英測量系統
Automatic Quartz Crystal Final Sort System With PI



* High speed DLD measurement (10 points DLD measuring time approx. 0.5 sec)
* Microsoft Windows. operation allows high quality graph and report printout
* Full Network Analyzer Configuration with Built-in Frequency synthesizer and vector
* High accuracy PI-Network Measurement compatible to IEC444
* Frequency range : 1 to 120 MHz
* Measurement throughput : Typical 5500 crystals / hr (depend on crystal Q factor)

STOCK CODE : 646-012 PRICE : CALL

KH-3100
石英測量系統
Automatic Quartz Crystal Final Sort System With PI



* High speed DLD measurement (10 points DLD measuring time approx. 0.5 sec)
* Microsoft Windows. operation allows high quality graph and report printout
* Full Network Analyzer Configuration with Built-in Frequency synthesizer and vector
* High accuracy PI-Network Measurement compatible to IEC444
* Frequency range : 1 to 240 MHz
* Measurement throughput : Typical 5500 crystals / hr (depend on crystal Q factor)

STOCK CODE : 646-013 PRICE : CALL

We welcome any inquiry for products not appear in this catalog

電工安全計 Electrical Safety Tester — KIKUSUI

TOS5051A
抗電壓儀
Withstanding Voltage Tester



* Complies with various safety standards
* AC/DC output (0 to 5 kV)
* Digital voltmeter and ammeter
* Equipped with remote control function
* Various signal outputs
* Automatic discharge function (during DC operation)

STOCK CODE : 645-672 PRICE : HK$ 16,665.00

TOS5052
抗電壓儀
Withstanding Voltage Tester



* Rise-time control function
* Automatically increase test voltage to a specified level as required by these standards
* High-capacity power supply with a maximum rated output of 500VA (5 kV at 100 mA). (Maximum test time : 30 min)
* Perform withstand voltage tests of electronic equipment and components

STOCK CODE : 645-855 PRICE : HK$ 29,925.00

TOS5101
抗電壓儀
Withstanding Voltage Tester



* Complies with various safety standards
* AC/DC output (0 to 10 kV)
* Digital voltmeter and ammeter
* Equipped with remote control function
* Various signal outputs
* Automatic discharge function (during DC operation)

STOCK CODE : 645-856 PRICE : HK$ 33,075.00

TOS6200
接地內阻計
Earth Continuity Tester



* High accuracy
* Equipped with standard GPIB and RS-232C interfaces
* Contact check function that identifies the connection of the device being tested (by current detection) before testing
* A test current for earth continuity testing has been made constant
* Offset canceling function that cancels resistance values

STOCK CODE : 645-854 PRICE : HK$ 21,862.00

直流電源供應 DC Power Supply — KIKUSUI

PMC18-1A
直流電源供應 (CV/CC)
DC Power Supply (CV/CC)



* 0-18V, 0-1A
* Simultaneous digital display of voltage and current values
* GPIB control by combining with the power supply controllers
* External analog remote control of voltage and current
* 10-turn potentiometer for setting of voltage and current

STOCK CODE : 645-257 PRICE : HK$ 3,500.00

PMC18-2A
直流電源供應 (CV/CC)
DC Power Supply (CV/CC)



* 0-18V, 0-2A
* Simultaneous digital display of voltage and current values
* GPIB control by combining with the power supply controllers
* External analog remote control of voltage and current
* 10-turn potentiometer for setting of voltage and current

STOCK CODE : 645-578 PRICE : HK$ 3,600.00

Information in this document is subject to change without notice. Other products and companies referred to herein are trademarks or registered trademarks of their respective companies or mark holders.