高可靠直流電源供應
High Reliability DC Power Supply KIKUSUI

PAN160-7A
高可靠直流電源供應
High Reliability DC Power Supply

* Constant voltage output (CV) : 0 to 160V
* Constant current output (CC) : 0 to 7A
* Low temperature drift
* Quick transient response
* Units are suitable for use in a range of fields including research and development, quality control, and production

STOCK CODE : 645-816 PRICE : HK$ 23,513.00

PAN250-2.5A
高可靠直流電源供應
High Reliability DC Power Supply

* Constant voltage output (CV) : 0 to 250V
* Constant current output (CC) : 0 to 2.5A
* Low temperature drift
* Quick transient response
* Units are suitable for use in a range of fields including research and development, quality control, and production

STOCK CODE : 645-815 PRICE : HK$ 15,675.00

PAN250-4.5A
高可靠直流電源供應
High Reliability DC Power Supply

* Constant voltage output (CV) : 0 to 250V
* Constant current output (CC) : 0 to 4.5A
* Low temperature drift
* Quick transient response
* Units are suitable for use in a range of fields including research and development, quality control, and production

STOCK CODE : 645-814 PRICE : HK$ 26,400.00

PAN350-3.5A
高可靠直流電源供應
High Reliability DC Power Supply

* Constant voltage output (CV) : 0 to 350V
* Constant current output (CC) : 0 to 3.5A
* Variable output, switching power supplies
* Reliability testing of electronic components
* Portable with an improved space factor making them suitable for system mounting

STOCK CODE : 645-813 PRICE : HK$ 34,650.00

PAN600-2A
高可靠直流電源供應
High Reliability DC Power Supply

* Constant voltage output (CV) : 0 to 600V
* Constant current output (CC) : 0 to 2A
* Variable output, switching power supplies
* Reliability testing of electronic components
* Portable with an improved space factor making them suitable for system mounting

STOCK CODE : 645-812 PRICE : HK$ 34,650.00

雙向追蹤直流電源供應
Dual-Tracking DC Power Supply KIKUSUI

PMR18-1.3TR
雙向追蹤直流電源供應
Dual-Tracking DC Power Supply

* Dual-tracking function capable of varying positive and negative voltages simultaneously
* Preset memory function (three memories) for ease of use and convenience, even in manual operation
* Constant voltage output : 0 to +18V(CH1), 0 to -18V(CH2), 0 to +6V(CH3)
* Constant current output : 0 to +1.3A(CH1), 0 to -1.3A(CH2), 0 to +5A(CH3)

STOCK CODE : 645-844 PRICE : HK$ 13,200.00

雙向追蹤直流電源供應
Dual-Tracking DC Power Supply KIKUSUI

PMR18-2.5DU
雙向追蹤直流電源供應
Dual-Tracking DC Power Supply

* Dual-tracking function capable of varying positive and negative voltages simultaneously
* Preset memory function (three memories) for ease of use and convenience, even in manual operation
* Constant voltage output : 0 to +18V(CH1), 0 to -18V(CH2)
* Constant current output : 0 to +2.5A(CH1), 0 to -2.5A(CH2)

STOCK CODE : 645-846 PRICE : HK$ 11,963.00

PMR24-1QU
雙向追蹤直流電源供應
Dual-Tracking DC Power Supply

* Dual-tracking function capable of varying positive and negative voltages simultaneously
* Preset memory function (three memories) for ease of use and convenience, even in manual operation
* Constant voltage output : 0 to +24V(CH1), 0 to -24V(CH2), 0 to +12V(CH3), 0 to -12V(CH4)
* Constant current output : 0 to +1A(CH1), 0 to -1A(CH2), 0 to +1.5A(CH3), 0 to -1.5A(CH4)

STOCK CODE : 645-842 PRICE : HK$ 13,200.00

PMR25-1TR
雙向追蹤直流電源供應
Dual-Tracking DC Power Supply

* Dual-tracking function capable of varying positive and negative voltages simultaneously
* Preset memory function (three memories) for ease of use and convenience, even in manual operation
* Constant voltage output (CV) : 0 to +25V(CH1), 0 to -25V(CH2), 0 to +6V(CH3)
* Constant current output (CC) : 0 to +1A(CH1), 0 to -1A(CH2), 0 to +5A(CH3)

STOCK CODE : 645-843 PRICE : HK$ 13,200.00

PMR35-1.2DU
雙向追蹤直流電源供應
Dual-Tracking DC Power Supply

* Dual-tracking function capable of varying positive and negative voltages simultaneously
* Preset memory function (three memories) for ease of use and convenience, even in manual operation
* Constant voltage output (CV) : 0 to +35V(CH1), 0 to -35V(CH2)
* Constant current output (CC) : 0 to +1.2A(CH1), 0 to -1.2A(CH2)

STOCK CODE : 645-845 PRICE : HK$ 11,963.00

www.icmaster.com.hk



試驗裝置
Tester KYORITSU

KYORITSU 4105A
數字量式接地測試器
Digital Earth Tester

* Comply to IEC61010-1 safety standard
* Capable of measuring earth voltage
* Automatic warning when resistance of auxiliary earth spikes is in excess of tolerance
* 2mA measuring current permits earth resistance tests without tripping earth leakage current breakers in the circuit under test

STOCK CODE : 646-139 PRICE : HK$ 1,300.00

KYORITSU 6010A
迴路 + 漏電測試器
Loop & RCD Tester

* Integral overload protection on internal continuity and insulation test circuitry
* Allow fast & safe discharge of electrical energy stored in capacitive circuits
* 500VDC test voltage for insulation tests
* 200mA short circuit current on continuity ranges
* Measuring ranges: 0~19.99 and 10.0~199.9MΩ (2 auto ranges)

STOCK CODE : 645-720 PRICE : HK$ 1,800.00

KYORITSU 6050
迴路 + 漏電測試器
Loop & RCD Tester

* Loop impedance 20/2000Ωmeasurement
* Carry out a test current of 15mA to avoid RCD trip
* RCD test at 0 and 180 degree phase angle
* RCD Ramp test to indicate the actual tripping current
* Stored data can be transferred to PC via Optical Adapter Model 8212

STOCK CODE : 647-630 PRICE : HK$ 2,800.00

KYORITSU 2004
AC/DC 數字量電源鉗錶
AC/DC Digital Clamp Meters

* Smallest clamp meter capable of AC and DC current measurements
* Current Range : 20/200A(AC or DC)
* Resolution: Minimum of 0.01A AC/DC
* Voltage measurement range : 500VAC or 200VDC
* Resistance measurement range : 200Ω
* Conductor Size: Ø19mm max

STOCK CODE : 646-888 PRICE : HK$ 1,404.00

KYORITSU 2033
袖珍式電源鉗錶
Mini Clamp Meter

* Smallest clamp meter capable of AC and DC current measurements
* Resolution: 0.01A AC/DC
* Auto zero function to allow one touch zero adjustment
* Frequency Response: DC, 20 ~ 1kHz
* Withstand Voltage: 3700VAC for 1 minute

STOCK CODE : 647-554 PRICE : HK$ 880.00

KYORITSU 8031
相位指示器
Phase Indicator

* Wide 3-phase Voltage Range : From 110 to 600 VAC
* Check the presence of open phase
* Check the phase sequence
* Indication : By rotating disk and lamps on the panel
* Safety standard: IEC61010-1 CAT.III 600V Pollution Degree 2

STOCK CODE : 645-739 PRICE : HK$ 225.00

Information in this document is subject to change without notice. Other products and companies referred to herein are trademarks or registered trademarks of their respective companies or mark holders.