PFC系列
PFC Series

SP-75 Series
75瓦特單組
75 Watt Single
* Input voltage range : 85~264VAC ; 47-63Hz
* Output voltage : Refer to table (±10% ADJ.)
* Overload protection : 105%~135% constant current limiting, auto recovery
* Withstand voltage : I/P-O/P: 3KV, I/P-FG:1.5KV, OP-FG:0.5KV


CASE:907 155x 150x 86mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
SP-75-3.3	3.3V, 15A	644-627	351.00
SP-75-5	5V, 15A	644-628	351.00
SP-75-7.5	7.5V, 10A	644-629	351.00
SP-75-12	12V, 6.25A	644-630	351.00

SP-100 Series
100瓦特單組
100 Watt Single
* Input voltage range : 85~264VAC ; 47-63Hz
* Output voltage : Refer to table (±10% ADJ.)
* Overload protection : 105%~150% constant current limiting, auto recovery
* Withstand voltage : I/P-O/P: 3KV, I/P-FG:1.5KV, OP-FG:0.5KV


CASE:915 179x 99x 45mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
SP-100-3.3	3.3V, 20A	644-636	384.00
SP-100-5	5V, 20A	644-637	384.00
SP-100-7.5	7.5V, 13.5A	644-638	384.00
SP-100-12	12V, 8.5A	644-639	384.00

SP-150 Series
150瓦特單組
150 Watt Single
* Input voltage range : 85~264VAC ; 47-63Hz
* Output voltage : Refer to table (±10% ADJ.)
* Overload protection : 105%~135% constant current limiting, auto recovery
* Withstand voltage : I/P-O/P: 3KV, I/P-FG:1.5KV, OP-FG:0.5KV


CASE:916A 199x 99x 50mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
SP-150-3.3	3.3V, 30A	644-645	430.00
SP-150-5	5V, 30A	644-646	430.00
SP-150-7.5	7.5V, 20A	644-647	430.00
SP-150-12	12V, 12.5A	644-648	430.00

SP-200 Series
200瓦特單組
200 Watt Single
* Input voltage range : 85~264VAC ; 47-63Hz
* Output voltage : Refer to table (±10% ADJ.)
* Overload protection : 105%~135% constant current limiting, auto recovery
* Withstand voltage : I/P-O/P: 3KV, I/P-FG:1.5KV, OP-FG:0.5KV


CASE:916B 199x 99x 50mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
SP-200-3.3	3.3V, 40A	644-654	515.00
SP-200-5	5V, 40A	644-655	515.00
SP-200-7.5	7.5V, 26.6A	644-656	515.00
SP-200-12	12V, 16.7A	644-657	515.00

SP-300 Series
300瓦特單組
300 Watt Single
* Input voltage : 88~264VAC universal input
* Input current/frequency : 4A/ 115V, 2A/ 230V; 47-63Hz
* Inrush current : 18A/ 115V, 36A/ 230V
* Overload protection : 105%~135% output pulsing mode
* Withstand voltage : I/P-O/P: 3KV, I/P-FG:1.5KV, 1min


CASE:912 230x 115x 50mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
SP-300-5	5V, 50A	644-663	768.00
SP-300-7.5	7.5V, 34A	644-664	768.00
SP-300-12	12V, 24A	644-665	768.00
SP-300-13.5	13.5V, 21A	644-666	768.00

PFC系列
PFC Series

SP-500 Series
500瓦特單組
500 Watt Single
* Input voltage : 88~264VAC universal input
* Input current/frequency : 7A/ 115V, 3.5A/ 230V; 47-63Hz
* Inrush current : 18A/ 115V, 36A/ 230V
* Overload protection : 105%~135% output constant limiting
* Withstand voltage : I/P-O/P:3KV, I/P-FG:1.5KV, 1min.


CASE:910 185x 120x 92mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
SP-500-12	12V, 40A	644-671	935.00
SP-500-13.5	13.5V, 36A	644-672	935.00
SP-500-15	15V, 32A	644-673	935.00
SP-500-24	24V, 20A	644-674	935.00
SP-500-27	27V, 0~18A	644-675	935.00

QP-200 Series
200瓦特四組輸出
200W Quad Output
* Input Voltage range: Universal AC input, Full range
* forced air cooling by built-in DC fan
* CH1,2 can be adjustable from -5 ~ +10%
* Built-in remote sense function for CH1,2


CASE: 912 230x 115x 50 mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
QP-200D	5,12,24V,-12V / 15,4,3,0.7A	648-608	690.00

平行系列
Parallel Series

PSP-300 Series
300瓦特平行
300 Watt Parallel
* Input voltage : 88~264VAC universal input
* Input current/frequency : 4.5A/ 115V, 2.3A/ 230V; 47-63Hz
* Inrush current : 18A/ 115V, 36A/230V
* Overload protection : 105%~135% output constant limiting
* Withstand voltage : I/P-O/P:3KV, I/P-FG:1.5KV, 1min.


CASE:910 185x 120x 92mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
PSP-300-12	12V, 25A	644-677	900.00
PSP-300-13.5	13.5V, 22A	644-678	900.00
PSP-300-24	24V, 12.5A	644-679	900.00
PSP-300-27	27V, 11A	644-680	900.00

PSP-500 Series
500瓦特平行
500 Watt Parallel
* Input voltage : 88~264VAC universal input
* Input current/frequency : 7A/ 115V, 3.5A/ 230V; 47-63Hz
* Inrush current : 20A/ 115V, 40A/ 230V
* Overload protection : 105%~135% output constant limiting
* Withstand voltage : I/P-O/P:3KV, I/P-FG:1.5KV, O/P-FG:0.5KV, 1min.



MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
PSP-500-12	12V, 41.5A	644-682	1,287.00
PSP-500-13.5	13.5V, 37A	644-683	1,287.00
PSP-500-24	24V, 20.8A	644-684	1,287.00
PSP-500-27	27V, 18.5A	644-685	1,287.00

SCN-600 & 800 Series
600~800W單組輸出平行
600 ~ 800W Single Output With Parallel
* Input voltage : 90~130V/ 180~260VAC selected by sw. (180~260VAC for SCN-800 series)
* Input current : 5.5A @230VAC for 600W ; 7.5A @230VAC for 800W
* Withstand voltage : I/P-O/P, I/P-FG:1250VAC for 1 min.


291x 132x 68mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
SCN-600-3.3	3.3V, 100A	645-114	1,545.00
SCN-600-05	5V, 100A	644-687	1,545.00
SCN-800-12	12V, 66A	644-692	1,545.00
SCN-800-15	15V, 54A	644-693	1,545.00

平行系列
Parallel Series

SCN-1K5 Series
1500W單組輸出平行
1500W Single Output With Parallel
* Input voltage : 180~260VAC ;1φ3 wire
* Input frequency : 47-63Hz
* Input current : 12A @230VAC
* Withstand voltage : I/P-O/P, I/P-FG:1500VAC for 1 min.


291x 132x 132mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
SCN-1K5-12	12V, 125A	644-702	3,334.00
SCN-1K5-15	15V, 100A	644-703	3,334.00
SCN-1K5-24	24V, 62.5A	644-704	3,334.00
SCN-1K5-48	48V, 32A	644-705	3,334.00


SCN-2K0 Series
2KW單組輸出平行
2KW Single Output With Parallel
* Input voltage : 200~260VAC ;3φ3 wire
* Input frequency : 47-63Hz
* Input current : 9.5A @230VAC; 1φ
* Withstand voltage : I/P-O/P, I/P-FG:1250VAC for 1 min.


320x 212x 134mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
SCN-2K0-05	5V, 250A	644-706	6,120.00
SCN-2K0-12	12V, 167A	644-707	6,120.00
SCN-2K0-15	15V, 13.4A	644-708	6,120.00
SCN-2K0-24	24V, 83.5A	644-709	6,120.00


G2 系列
G2 Series

S-25 Series
25W單組輸出
25W Single Output Switching
* Input voltage: 85~264VAC; 120~370VDC
* AC inrush current: 30A at 230VAC
* Overload, over voltage protection
* UL, TUV, EMC standards
* Connection: 5P/ 9.5mm pitch terminal block


CASE: 905 99x 97x 36 mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
S-25-24	24V, 0~1.1A	644-556	300.00

S-40 Series
40W單組輸出
40W Single Output Switching
* Input voltage: 85~264VAC; 120~370VDC
* AC inrush current: 60A at 230VAC
* Overload, over voltage protection
* UL, TUV, EMC standards
* Connection: 5P/ 9.5mm pitch terminal block


CASE: 903 129x 98x 36 mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
S-40-5	5V, 0~8A	644-162	348.00
S-40-24	24V, 0~1.8A	644-165	348.00

S-60 Series
60W單組輸出
60W Single Output Switching
* Input voltage: 85~264VAC; 120~370VDC
* AC inrush current: 60A at 230VAC
* Overload, over voltage protection
* UL, TUV, EMC standards
* Connection: 5P/ 9.5mm pitch terminal block



CASE: 901 159x 97x 38 mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
S-60-12	12V, 0~ 5A	644-347	388.00
S-60-24	24V, 0~ 2.5A	644-348	388.00

Information in this document is subject to change without notice. Other products and companies referred to herein are trademarks or registered trademarks of their respective companies or mark holders.

G2 系列
G2 Series


S-100F Series
100W單組輸出
100W Single Output Switching



* Input voltage: 88~132VAC or 176~264VAC
* AC inrush current: 60A at 230VAC
* Overload, over voltage protection
* UL, TUV, EMC standards
* Connection: 7P/ 9.5mm pitch terminal block

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
S-100F-12	12V, 0~ 8.5A	644-577	420.00
S-100F-24	24V, 0~ 4.5A	644-354	450.00

S-150 Series
150W單組輸出
150W Single Output Switching



CASE:906 199x 110x 50mm

* Input voltage: 88~132VAC / 176~264VAC selected by sw.
* Input frequency: 47-63Hz
* Inrush current: cold start, 35A
* Overload protection: 105%~150% output shutdown
* Withstand boltage : I/P-O/P: 3KV, I/P-F/G: 1.5KV, 1 min.

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
S-150-5	5V, 30A	644-580	280.00
S-150-7.5	7.5V, 20A	644-581	280.00
S-150-9	9V, 16.7A	644-582	280.00
S-150-12	12V, 12.5A	644-266	280.00
S-150-15	15V, 0~10A	644-583	280.00

S-240 Series
240W單組輸出
240W Single Output Switching



CASE:911 205x 93x 65mm

* Input voltage : 88~132VAC / 176~264VAC auto. change
* Input frequency : 47-63Hz
* Inrush current : 18A/ 115V, 36A/ 230V
* Overload protection : 105%~135% rated output power
* Withstand voltage : I/P-O/P: 3KV, I/P-FG: 1.5KV, 1min.

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
S-240-5	5V, 40A	644-600	588.00
S-240-7.5	7.5V, 30A	644-601	588.00
S-240-12	12V, 18A	644-602	588.00
S-240-15	15V, 15A	644-603	588.00
S-240-24	24V, 0~10A	644-235	588.00

S-320 Series
320W單組輸出
320W Single Output Switching




CASE:912 230x 115x 50mm

* Input voltage : 88~132VAC / 176~264VAC selected by sw.
* Input frequency : 47-63Hz
* Inrush current : 20A/ 115V, 40A/ 230V
* Overload protection : 105%~135% rated output power
* Withstand voltage : I/P-O/P: 3KV, I/P-FG: 1.5KV, 1min.

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
S-320-5	5V, 50A	644-606	542.00
S-320-7.5	7.5V, 36A	644-607	542.00
S-320-12	12V, 25A	644-608	542.00
S-320-13.5	13.5V, 22A	644-609	542.00

T-40 Series
40W三組輸出
40W Triple Output Switching




CASE:903 129x 98x 38mm

* Input voltage : 85~264VAC; 120~370VDC
* Input frequency : 47-63Hz
* Inrush current : Cold start, 20A/ 115V, 40A/ 230V
* Withstand voltage : I/P-O/P: 3KV, I/P-FG: 1.5KV, 1 min
* Overload protection : 105%~150%/ 115VAC rated output power

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
T-40A	5,12,-5V / 3,2,0.5A	644-737	203.00
T-40B	5,12,-12V / 3,2,0.5A	644-738	203.00
T-40C	5,15,-15V / 3,1.5,0.5A	644-267	203.00

G2 系列
G2 Series

T-60 Series
60W三組輸出
60W Triple Output Switching




CASE:901 159x 97x 38mm

* Input voltage : 85~264VAC/ 120~370VDC
* Input frequency : 47-63Hz
* Inrush current : Cold start, 30A/ 115V, 60A/ 230V
* Overload protection : 105%~150%/ 115VAC rated output power
* Withstand voltage : I/P-O/P: 3KV, I/P-FG: 1.5KV, 1 min

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
T-60A	5,12,-5V / 5,2.5,0.5A	644-743	310.00
T-60B	5,12,-12V / 5,2.5,0.5A	644-744	310.00
T-60C	5,15,-15V / 5,2,0.5A	644-236	310.00


T-120 Series
120W三組輸出
120W Triple Output Switching



* Input voltage: 88~132VAC or 176~264VAC
* Overload, over voltage protection
* UL, TUV, EMC standards
* Connection: 8P/9.5mm pitch terminal block

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
T-120D	5, 12, 24V / 12, 5, 2A	647-165	308.00

D-60 Series
60W雙組輸出
60W Dual Output Switching




CASE:901 159x 97x 38mm

* Input voltage : 85~264VAC; 120~370VDC
* Input frequency : 47-63Hz
* Inrush current : Cold start, 30A/ 115V, 60A/ 230V
* Overload protection : 105%~150% rated output power
* Withstand voltage : I/P-O/P: 3KV, I/P-FG: 1.5KV, 1 min

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
D-60A	5, 12V / 4, 3A	644-718	300.00
D-60B	5, 24V / 3,1.8A	644-719	300.00
ID-60B	5, 24V / 3, 1.8A (Isolated O/P & Gnd for CH1 & CH2)	644-720	331.00

Q-60 Series
60W四組輸出
60W Quad Output Switching




159x 97x 38mm

* Input voltage : 85~264VAC; 120~370VDC
* Input frequency : 47-63Hz
* Inrush current : Cold start, 18A/ 115V, 36A/ 230V
* Overload protection : 105%~150%/ 115VAC rated output power
* Withstand voltage : I/P-O/P: 3KV, I/P-FG: 1.5KV, 1 min.

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
Q-60B	5,12,-5,-12V / 5.5,2,0.5.0.5A	646-581	300.00
Q-60C	5,15,-5,-15V / 5.5,1.5,0.5,0.5A	646-580	300.00
Q-60D	5,12,24,-12V / 4,1,1,0.5A	644-711	300.00

D-120 Series
120W雙組輸出
120W Dual Output Switching




CASE:906 199x 110x 50mm

* Input voltage : 88~132VAC/ 176~264VAC selected by sw.
* Input frequency : 47-63Hz
* Inrush current : Cold start, 35A
* Overload protection : 105%~135% rated output power
* Withstand voltage : I/P-O/P: 3KV, I/P-FG: 1.5KV, 1 min.

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
D-120A	5, 12V / 12, 5A	644-160	325.00
D-120B	5, 24V / 6, 4A	644-161	325.00

G2 系列
G2 Series

Q-120 Series
120W四組輸出
120W Quad Output Switching



199x 110x 50mm

* Input voltage : 88~132VAC/ 176~264VAC selected by sw.
* Input frequency : 47-63Hz
* Inrush current : Cold start, 35A
* Overload protection : 105%~135% rated output power
* Withstand voltage : I/P-O/P: 3KV, I/P-FG: 1.5KV, 1min.

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
Q-120B	5,12,-5,-12V / 11,4,1,1A	644-158	362.00
Q-120C	5,15,-5,-15V / 10,3.5,1,1,A	644-712	362.00
Q-120D	5,12,24,-12V / 8,2,2,2,A	644-151	362.00

S-150 Series
150W單組輸出
150W Single Output Switching



MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
S-150-24	24V, 6.5 A	644-353	280.00

G1 系列
G1 Series

S-15 Series
15W單組輸出
15W Single Output Switching




CASE:905 99x 97x 35mm

* Input voltage : 85~132VAC / 170~264VAC selected by sw.
* Input frequency : 47-63Hz
* nrush current : Cold start, 15A/ 115V, 30A/ 230V
* Overload protection : 105%~150% rated output power
* Withstand voltage : I/P-O/P: 1.5KV, I/P-FG: 1.5KV, 1min.

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
S-15-5	5V, 3A	644-159	100.00
S-15-12	12V, 1.3A	644-294	100.00
S-15-24	24V, 0.7A	644-552	100.00

S-35 Series
35W單組輸出
35W Single Output Switching




CASE:903 129x 98x 38mm

* Input voltage : 85~132VAC / 170~264VAC selected by sw.
* Input frequency : 47-63Hz
* Inrush current : Cold start, 15A/ 115V, 30A/ 230V
* Overload protection : 105%~150% rated output power
* Withstand voltage : I/P-O/P: 1.5KV, I/P-FG: 1.5KV, 1min.

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
S-35-5	5V, 7A	644-557	122.00
S-35-12	12V, 3A	644-558	122.00
S-35-15	15V, 2.4A	644-559	122.00
S-35-24	24V, 1.5A	644-560	122.00

S-50 Series
50W單組輸出
50W Single Output Switching



CASE:901 159x 97x 38mm


* Input voltage : 85~132VAC / 170~264VAC selected by sw.
* Input frequency : 47-63Hz
* Inrush current : Cold start, 18A/ 115V, 36A/ 230V
* Overload protection : 105%~150% rated output power
* Withstand voltage : I/P-O/P: 1.5KV, I/P-FG: 1.5KV, 1min.

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
S-50-5	5V, 10A	644-361	145.00
S-50-12	12V, 4.2A	644-561	145.00
S-50-15	15V, 3.4A	644-562	145.00
S-50-24	24V, 2.1A	644-563	145.00

Information in this document is subject to change without notice. Other products and companies referred to herein are trademarks or registered trademarks of their respective companies or mark holders.

G1 系列 G1 Series

S-100 Series
100W單組輸出
100W Single Output Switching
* Input voltage : 85~132VAC / 180~264VAC selected by sw.
* Input frequency : 47-63Hz
* Inrush current : Cold start, 30A/ 115V, 60A/ 230V
* Overload protection : 105%~150% rated output power (S-100-7.5 150% ~ 200%)
* Withstand voltage : I/P-O/P: 1.5KV, I/P-FG: 1.5KV,1min.


CASE:905 199x 98x 38mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
S-100-3	3V, 20A	645-113	236.00
S-100-5	5V, 20A	644-374	236.00
S-100-7.5	7.5, 13.6A	644-577	236.00
S-100-10	10V, 10A	644-568	236.00
S-100-12	12V, 0~8.5A	644-569	236.00

S-201 Series
200W單組輸出
200W Single Output Switching
* Input voltage : 90~132VAC / 180~264VAC selected by sw.
* Input frequency : 47-63Hz
* Inrush current : Cold start, 25A/ 115V, 50A/ 230V
* Overload protection : 105%~135% rated output power
* Withstand voltage : I/P-O/P: 1.5KV, I/P-FG: 1.5KV, 1min.


CASE:912B 230x 115x 50mm


MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
S-201-5	5V, 40A	644-592	330.00
S-201-7.5	7.5V, 26.5A	644-593	330.00
S-201-12	12V, 16.5A	644-594	330.00
S-201-13.5	13.5V, 14.7A	644-595	330.00

S-350 Series
350W單組輸出
350W Single Output Switching
* Input voltage : 90~132VAC / 180~264VAC selected by sw.
* Input frequency : 47-63Hz
* Inrush current : Cold start,. 25A/ 115V, 50A/ 230V
* Overload protection : 105%~135% rated output power
* Withstand voltage : I/P-O/P: 1.5KV, I/P-FG: 1.5KV, 1min.


CASE:912 230x 115x 50mm


MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
S-350-5	5V, 50A	644-613	500.00
S-350-7.5	7.5V, 40A	644-614	500.00
S-350-12	12V, 29A	644-615	500.00
S-350-13.5	13.5V, 25.8A	644-616	500.00

D-30 Series
30W雙組輸出
30W Dual Output Switching
* Input voltage : 85~132VAC/ 170~264VAC selected by sw.
* Input frequency : 47-63Hz
* Inrush current : Cold start, 18A/ 115V, 36A/ 230V
* Overload protection : 105%~150% rated output power
* Withstand voltage : I/P-O/P: 1.5KV, I/P-FG: 1.5KV, 1 min.


CASE:903 129x 98x 38mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
D-30A	5, 12V / 4, 1A	644-495	160.00
D-30B	5, 24V / 2.2, 1A	644-714	160.00
ID-30B	(O/P is isolated from the other)	644-715	160.00


T-30 Series
30W三組輸出
30W Triple Output Switching
* Input voltage : 85~132VAC/ 170~264VAC selected by sw.
* Input frequency : 47-63Hz
* Inrush current : Cold start, 15A/ 115V, 30A/ 230V
* Overload protection : 105%~150% rated output power
* Withstand voltage : I/P-O/P: 1.5KV, I/P-FG: 1.5KV, 1 min.


CASE:903 129x 98x 38mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
T-30A	5,12,-5V / 3,1,0.5A	644-735	160.00
T-30B	5,12,-12V / 3,1,0.5A	644-736	160.00


G1 系列 G1 Series

D-50 Series
50W雙組輸出
50W Dual Output Switching
* Input voltage : 85~132VAC/ 170~264VAC selected by sw.
* Input frequency : 47-63Hz
* Inrush current : Cold start, 18A/ 115V, 36A/ 230V
* Overload protection : 105%~150% rated output power
* Withstand voltage : I/P-O/P: 1.5KV, I/P-FG: 1.5KV, 1 min.


CASE:901 159x 97x 38mm


MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
D-50A	5, 12V / 6, 2A	644-716	175.00
D-50B	5, 24V / 6, 1A	644-717	175.00

ID-50 Series
50W雙組獨立輸出
50W Dual Isolated Output Switching
* Input voltage : 85~264VAC/ 120~370VDC
* Input frequency : 47-63Hz
* Inrush current : Cold start, 18A/ 115V, 36A/ 230V
* Overload protection : 105%~150% rated output power
* Withstand voltage : I/P-O/P: 1.5KV, I/P-FG: 1.5KV, 1 min.


CASE:901 159x 97x 38mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
ID-50A	5, 5V / 6, 2A	644-721	275.00
ID-50B	13.5, 13.5V / 1.8, 1.8A	644-722	275.00
ID-50C	27, 27V / 0.9A, 0.9A	644-723	275.00
ID-50D	5, 13.5V / 5, 1.7A	644-724	275.00

T-50 Series
50W三組輸出
50W Triple Output Switching
* Input voltage : 85~132VAC/ 170~264VAC selected by sw.
* Input frequency : 47-63Hz
* Inrush current : Cold start, 20A/ 115V, 40A/ 230V
* Overload protection : 105%~150% rated output power
* Withstand voltage : I/P-O/P: 1.5KV, I/P-FG: 1.5KV, 1 min.


CASE:901 159x 97x 38mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
T-50A	5,12,-5V / 7,1,1A	644-739	191.00
T-50B	5,12,-12V / 5,1,1A	644-740	191.00
T-50C	5,15,-15V / 4,1,1A	644-741	191.00
T-50D	5,12,24V / 3,1,1A	644-742	191.00

線路板型 On Board Type

OFM-5000 Series
5W AC/DC 線路板型
5W AC/DC On Board Type
* Input voltage : 85~264VAC; 120~370VDC
* Input frequency : 47-440Hz
* Inrush current : Cold start, 40A/ 230V
* Overload protection : Above 150% rated output power
* Withstand voltage : I/P-O/P: 3.0KVAC


5W : 58x 45x 21mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
OFM-5001	5V, 1A	644-763	155.00
OFM-5002	12V, 0.42A	644-764	155.00
OFM-5003	15V, 0.33A	644-765	155.00
OFM-5005	24V, 0.23A	644-766	155.00

OFM-0100 Series
10W AC/DC 線路板型
10W AC/DC On Board Type
* Input voltage : 85~264VAC; 120~370VDC
* Input frequency : 47-440Hz
* Inrush current : Cold start, 25A/ 115V, 45A/ 230V
* Overload protection : Above 150% rated output power
* Withstand voltage : I/P-O/P: 3.0KVAC


10W : 65x 45x 21mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
OFM-0101	5V, 2A	644-767	170.00
OFM-0102	12V, 0.85A	644-768	170.00
OFM-0103	15V, 0.67A	644-769	170.00
OFM-0105	24V, 0.42A	644-770	170.00

線路板型 On Board Type

OFM-1500 Series
15W AC/DC 線路板型
15W AC/DC On Board Type
* Input voltage : 85~264VAC; 120~370VDC
* Input frequency : 47-440Hz
* Inrush current : Cold start, 25A/ 115V, 45A/ 230V
* Overload protection : Above 150% rated output power
* Withstand voltage : I/P-O/P: 3.0KVAC


15W : 70x 48x 21mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
OFM-1501	5V, 3A	644-771	195.00
OFM-1502	12V, 1.25A	644-772	195.00
OFM-1503	15V, 1A	644-773	195.00
OFM-1505	24V, 0.63A	644-774	195.00

OFM-0200 Series
20W AC/DC 線路板型
20W AC/DC On Board Type
* Input voltage : 85~264VAC; 120~370VDC
* Input frequency : 47-440Hz
* Inrush current : Cold start, 25A/ 115V, 45A/ 230V
* Overload protection : Above 150% rated output power
* Withstand voltage : I/P-O/P: 3.0KVAC


20W : 89x 51x 21mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
OFM-0201	5V, 4.4A	644-775	218.00
OFM-0202	12V, 1.8A	644-776	218.00
OFM-0203	15V, 1.4A	644-777	218.00
OFM-0205	24V, 0.92A	644-778	218.00

通用PCB型 General PCB

PS-25 Series
25W單組輸出
25W Single Outputs Switching
* Input voltage range : 85~264VAC; 120~370VDC
* Input frequency : 47-63Hz
* Inrush current : Cold start, 20A/ 115V, 40A/ 230V
* Overload protection : >105% rated output power
* Withstand voltage : I/P-O/P: 3KV, I/P-FG: 1.5KV, 1 min.


107x 61x 30mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
PS-25-3.3	3.3V, 5A	644-749	160.00
PS-25-5	5V, 5A	644-287	160.00
PS-25-7.5	7.5V, 3.3A	644-750	160.00
PS-25-12	12V, 2.1A	644-288	160.00

PD-25 Series
25W雙組輸出
25W Dual Outputs Switching
* Input voltage : 90~132VAC / 180~264VAC selected by sw.
* Input frequency : 47-63Hz
* Inrush current : Cold start, 20A/ 115V, 40A/ 230V
* Overload protection : 105%~135% rated output power
* Withstand voltage : I/P-O/P: 1.5KV, I/P-FG: 1.5KV, 1 min.


107x 61x 30mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
PD-25A	5, 12V / 2.5, 1.5A	644-300	178.00
PD-25B	5, 24V / 2, 1A	644-301	178.00
PD-2505	5, -5V / 3, 2.5A	644-754	218.00
PD-2512	12, -12V / 1.2, 1.2A	644-755	218.00

PS-45 Series
45W單組輸出
45W Single Outputs Switching
* Input voltage range : 90~264VAC; 120~370VDC
* Input frequency : 47-440Hz
* Inrush current : Cold start, 20A/ 115V, 40A/ 230V
* Overload protection : 53~75W rated output power
* Withstand voltage : I/P-O/P: 3KV, I/P-FG: 1.5KV



127x 76.2x 30mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
PS-45-3.3	3.3V / 10.7A	644-758	173.00
PS-45-5	5V / 10.5A	644-290	173.00
PS-45-7.5	7.5V / 7A	644-759	173.00
PS-45-12	12V / 4.4A	644-291	173.00

Information in this document is subject to change without notice. Other products and companies referred to herein are trademarks or registered trademarks of their respective companies or mark holders.

通用PCB型 General PCB

PD-45 Series
45W雙組輸出
45W Dual Outputs Switching
* Input voltage range : 90~264VAC; 120~370VDC
* Input frequency : 47-440Hz
* Inrush current : Cold start, 20A/ 115V, 40A/ 230V
* Overload protection : 53~75W rated output power
* Withstand voltage : I/P-O/P: 3KV, I/P-FG: 1.5KV


127x 76.2x 30mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
PD-45A	5, 12V / 5, 2.5A	644-295	192.00
PD-45B	5, 24V / 5, 1.8A	644-296	192.00

PT-45 Series
45W三組輸出
45W Triple Outputs Switching
* Input voltage range : 90~264VAC; 120~370VDC
* Input frequency : 47-440Hz
* Inrush current : Cold start, 20A/ 115V, 40A/ 230V
* Overload protection : 53~75W rated output power
* Withstand voltage : I/P-O/P: 3KV, I/P-FG: 1.5KV


127x 76.2x 30mm


MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
PT-45A	5,12,-5V / 5,2.5,0.5A	644-779	204.00
PT-45B	5,12,-5V / 5,2.5,0.5A	644-780	204.00
PT-45C	5,15,-15V / 5,2.3,0.5A	644-781	204.00

PT-4503
45W三組輸出
45W Triple Output Switching
* Input voltage range : 90~264VAC; 120~370VDC
* Input frequency : 47-440Hz
* Inrush current : Cold start, 20A/ 115V, 40A/ 230V
* Overload protection : 120~160% rated output power
* Withstand voltage : I/P-O/P: 3KV, I/P-FG: 1.5KV, O/P-FG: 0.5KV, 1 min.


127x 76.2x 30mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
PT-4503	3.3,5,12V / 5,7,1.2A	644-792	286.00

PT-6503
65W三組輸出
65W Triple Output Switching
* Input voltage range : 90~264VAC; 120~370VDC
* Input frequency : 47-440Hz
* Inrush current : Cold start, 20A/ 115V, 40A/ 230V
* Overload protection : 120~160% rated output power
* Withstand voltage : I/P-O/P: 3KV, I/P-FG: 1.5KV, O/P-FG: 0.5KV, 1 min.


127x 76.2x 40mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
PT-6503	3.3,5,12V / 7,10,1.2A	644-793	320.00

PS-65 Series
65W單組輸出
65W Single Outputs Switching
* Input voltage range : 90~264VAC; 120~370VDC
* Input frequency : 47-440Hz
* Inrush current : Cold start, 20A/ 115V, 40A/ 230V
* Overload protection : 73~105W rated output power
* Withstand voltage : I/P-O/P: 3KV, I/P-FG: 1.5KV, O/P-FG: 0.5KV, 1 min.


127x 76.2x 40mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
PS-65-3.3	3.3V /15.2A	644-782	192.00
PS-65-5	5V / 13.8A	644-304	192.00
PS-65-7.5	7.5V / 9.6A	644-784	192.00
PS-65-12	12V / 6A	644-278	192.00

通用PCB型 General PCB

PD-65 Series
65W雙組輸出
65W Dual Outputs Switching
* Input voltage range : 90~264VAC; 120~370VDC
* Input frequency : 47-440Hz
* Inrush current : Cold start, 20A/ 115V, 40A/ 230V
* Overload protection : 73~105W rated output power
* Withstand voltage : I/P-O/P: 3KV, I/P-FG: 1.5KV, O/P-FG: 0.5KV, 1 min.


127x 76.2x 40mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
PD-65A	5, 12V / 7, 3.2A	644-297	218.00
PD-65B	5, 24V / 6, 2.6A	644-298	218.00

PT-65 Series
65W三組輸出
65W Triple Outputs Switching
* Input voltage range : 90~264VAC; 120~370VDC
* Input frequency : 47-440Hz
* Inrush current : Cold start, 20A/ 115V, 40A/ 230V
* Overload protection : 73~105W rated output power
* Withstand voltage : I/P-O/P: 3KV, I/P-FG: 1.5KV, O/P-FG: 0.5KV, 1 min.


127x 76.2x 40mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
PT-65A	5,12,-5V / 7,3.2,0.7A	644-302	230.00
PT-65B	5,12,-12V / 7,3.2,0.7A	644-303	230.00
PT-65C	5,15,-15V / 7,2.6,0.7A	644-791	230.00
PT-65D	5,12,24V / 5,4,1.3A	645-115	230.00

PD-110 Series
100W雙組輸出
100W Dual Outputs Switching
* Input voltage range : 100~264VAC; 141~370VDC
* Input frequency : 47-63Hz
* Inrush current : Cold start, 30A/ 115V, 50A/ 230V
* Overload protection : 105%~135% rated output power
* Withstand voltage : I/P-O/P: 3.0KVAC, I/P-FG: 1.5KVAC, O/P-FG: 0.5KVAC, 1 min.


7"x 4.25"x 1.88"mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
PD-110A	5, 12V / 5, 6.5A	644-794	385.00
PD-110B	5, 24V / 5, 3.5A	644-795	385.00

PQ-100 Series
100W四組輸出
100W Quad Outputs Switching
* Input voltage range : 100~264VAC; 141~370VDC
* Input frequency : 47-63Hz
* Inrush current : Cold start, 30A/ 115V, 50A/ 230V
* Overload protection : 105%~135% rated output power
* Withstand voltage : I/P-O/P: 3.0KVAC, I/P-FG: 1.5KVAC, O/P-FG: 0.5KVAC, 1 min.


7"x 4.25"x 1.88"mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
PQ-100B	5,12,-5,-12V / 10,4.5,1,1A	644-796	416.00
PQ-100C	5,15,-5,-15V / 8,4,1,1A	644-377	416.00
PQ-100D	5,12,24,-12V / 5,4.5,2,1A	644-797	416.00
PQ-100E	5,12,15,24V / 8,3,1,1A	644-798	416.00

LPS-100 Series
100W LPS 單組輸出
100W LPS Single Output Switching
* Input voltage : 88~132VAC; 176~264VDC auto sw.
* Input frequency : 47-63Hz
* Inrush current : Cold start, 30A/ 115V, 60A/ 230V
* Overload protection : 105~140% rated O/P power, auto recovery
* Withstand voltage : I/P-O/P: 3KV, I/P-FG: 1.5KV, 1 min.


222x 62x 35mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
LPS-100-3.3	3.3V, 20A	644-807	410.00
LPS-100-5	5V, 20A	644-808	410.00
LPS-100-7.5	7.5V, 13.3A	644-809	410.00
LPS-100-12	12V, 8.4A	644-810	410.00

通用PCB型 General PCB

LPP-100 Series
100W LPP 單組輸出轉換式
100W LPP Single Output Switching
* Input voltage : 85~264VAC auto sw.
* Input frequency : 47-63Hz
* Inrush current : Cold start, 20A/ 115V, 40A/ 230V
* Overload protection : 105%~135% constant current limiting
* Withstand voltage : I/P-O/P: 3KV, I/P-FG: 1.5KV, 1 min.


222x 62x 63 mm

MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
LPP-100-3.3	3.3V / 20A	644-815	468.00
LPP-100-5	5V / 20A	644-816	468.00
LPP-100-7.5	7.5V / 13.3A	644-817	468.00
LPP-100-12	12V / 8.5A	644-818	468.00

LPP-150 Series
150W LPP 單組輸出轉換式
150W LPP Single Output Switching
* Input voltage : 85~264VAC / 120~370VDC
* Input frequency : 47-63Hz
* Inrush current : Cold start, 20A/ 115V, 40A/ 230V
* Overload protection : 105%~150% constant current limiting
* Withstand voltage : I/P-O/P: 3KV, I/P-FG: 1.5KV, 1 min.



MODEL	OUTPUT	STOCK CODE	PRICE (HK$)
LPP-150-3.3	3.3V / 30A	645-119	498.00
LPP-150-5	5V / 30A	645-120	498.00
LPP-150-7.5	7.5V / 20A	645-121	498.00
LPP-150-12	12V / 12.5A	645-122	498.00

ATX 電源 ATX Power

ATX-68A
微型 ATX PC 電源供應
150W Micro ATX PC Power Supply
* Input voltage : 100~132VAC/ 200~264VAC selected by sw.
* Protection : Short circuit / Over load
* Power good / fail signal
* Forced air cooling by built-in DC fan
* Approvals : UL/ CUL/ TUV/ CE



STOCK CODE : 645-130	PRICE : HK$ 300.00

模塊型 Module Type

SRS Series
0.5W DC-DC 單組輸出
0.5W DC-DC Regulated Single Output
* Voltage set point accuracy :±2% (MAX.)
* Load regulation :±1%
* Input reflected ripple : 120mVp-p
* Short protection : Momentary
* Switching frequency : 50KHz (MIN.)


0.89" x 0.39" x 0.33"

MODEL	I/P	O/P	STOCK CODE	PRICE (HK$)
SRS-0505	5V	5V	645-267	65.00
SRS-0509	5V	9V	645-268	65.00
SRS-0512	5V	12V	645-269	65.00
SRS-0515	5V	15V	645-270	65.00

SUS01 Series
1W DC-DC 單組輸出 (未濾波)
1W DC-DC Unregulated Single Output
* Voltage set point accuracy:±2% (MAX.) @full load; nominal line
* Load regulation :±8%
* Input reflected ripple : 100mVp-p
* Short protection : Momentary
* Switching frequency : 50KHz (MIN.)


0.89" x 0.39" x 0.33"mm

MODEL	I/P	O/P	STOCK CODE	PRICE (HK$)
SUS01L-05	5V	5V	645-283	56.00
SUS01L-09	5V	9V	645-284	56.00
SUS01L-12	5V	12V	645-285	56.00
SUS01L-15	5V	15V	645-286	56.00

Information in this document is subject to change without notice. Other products and companies referred to herein are trademarks or registered trademarks of their respective companies or mark holders.

模塊型 Module Type

SPR01 Series

1W DC-DC 單組輸出

1W DC-DC Regulated Single Output

* Voltage set point accuracy :±2% (MAX.)
* Load regulation :±1%
* Short protection : Momentary
* Switching frequency : 50KHz (MIN.)
* I/O isolation voltage : 1000 VDC (MIN.)



0.77" x 0.4" x 0.24"

MODEL	I/P	O/P	STOCK CODE	PRICE (HK$)
SPR01L-05	5V	5V	645-299	65.00
SPR01L-09	5V	9V	645-300	65.00
SPR01L-12	5V	12V	645-301	65.00
SPR01L-15	5V	15V	645-302	65.00

SCW03 Series

3W DC-DC 單組輸出

3W DC-DC Regulated Single Output

* Voltage set point accuracy :±2% (MAX.)
* Load regulation : Single±0.5%
* I/O isolation voltage : 1000 VDC (MIN.)
* I/O isolation resistance : 100MΩ(MIN.)



1.25" x 0.8" x 0.48"

MODEL	I/P	O/P	STOCK CODE	PRICE (HK$)
SCW03A-05	9-18V	5V	645-315	133.00
SCW03A-12	9-18V	12V	645-316	133.00
SCW03A-15	9-18V	15V	645-317	133.00
SCW03B-05	18-36V	5V	645-318	133.00

DCW03 Series

3W DC-DC 雙組輸出

3W DC-DC Regulated Daul Output

* 1000VDC I/O Isolation
* Input Pi network filter
* Protection: Short circuit / Overload
* Cooling by free air convection
* Low cost, high reliability



1.25" x 0.8" x 0.48"

MODEL	I/P	O/P	STOCK CODE	PRICE (HK$)
DCW03A-05	9-18V	±5V	645-324	142.00
DCW03A-12	9-18V	±12V	645-325	142.00
DCW03A-15	9-18V	±15V	645-326	142.00
DCW03B-05	18-36V	±5V	645-327	142.00

DCW05A-12

DC-DC 雙組輸出

2:1 Wide Input Range DC-DC Regulated Output

* DC Dual Output: ±12VDC, ±230mA
* DC input: 9~18VDC
* 1000VDC I/O isolation
* Protections: Short cirucit, over load, over voltage



STOCK CODE : 647-617 **PRICE : HK$ 142.00**

SLW05 Series

5W DC-DC 單組輸出

5W DC-DC Regulated Single Output

* Voltage set point accuracy :±2% (MAX.)
* Load regulation :±0.5%
* I/O isolation voltage : 1000 VDC (MIN.)
* I/O isolation resistance : 100MΩ(MIN.)



2" x 1" x 0.44"

MODEL	I/P	O/P	STOCK CODE	PRICE (HK$)
SLW05A-05	9-18V	5V	645-197	189.00
SLW05A-09	9-18V	9V	645-198	189.00
SLW05A-12	9-18V	12V	645-199	189.00
SLW05A-15	9-18V	15V	645-200	189.00

DLW05 Series

5W DC-DC 雙組輸出

5W DC-DC Regulated Dual Output

* Voltage set point accuracy :±2% (MAX.)
* Load regulation :±0.5%
* I/O isolation voltage : 1000 VDC (MIN.)
* I/O isolation resistance : 100MΩ(MIN.)



2" x 1" x 0.44"

MODEL	I/P	O/P	STOCK CODE	PRICE (HK$)
DLW05A-05	9-18V	5V	645-209	194.00
DLW05A-12	9-18V	12V	645-210	194.00
DLW05A-15	9-18V	15V	645-211	194.00
DLW05B-05	18-36V	5V	645-212	194.00

模塊型 Module Type

SKE10 Series

10W DC-DC 單組輸出

10W DC-DC Single Output

* Load regulation :±5%
* I/O isolation voltage : 1000 VDC (MIN.)
* I/O isolation resistance : 100MΩ(MIN.)



2" x 1" x 0.42"

MODEL	I/P	O/P	STOCK CODE	PRICE (HK$)
SKE10A-05	9-18V	5V	645-218	255.00
SKE10A-12	9-18V	12V	645-219	255.00
SKE10A-15	9-18V	15V	645-220	255.00
SKE10A-24	9-18V	24V	645-221	255.00

DKE10 Series

10W DC-DC 雙組輸出

10W DC-DC Dual Output

* Load regulation :±5%
* I/O isolation voltage : 1000 VDC (MIN.)
* I/O isolation resistance : 100MΩ(MIN.)



2" x 1" x 0.42"

MODEL	I/P	O/P	STOCK CODE	PRICE (HK$)
DKE10A-05	9-18V	±5V	645-230	266.00
DKE10A-12	9-18V	±12V	645-231	266.00
DKE10A-15	9-18V	±15V	645-232	266.00
DKE10A-24	9-18V	±24V	645-233	266.00

SKE-15 Series

15W DC-DC 單組輸出

15W DC-DC Single Output

* Load regulation :±0.5%
* I/O isolation voltage : 1000 VDC (MIN.)
* I/O isolation resistance : 100MΩ(MIN.)



2" x 2" x 0.42"

MODEL	I/P	O/P	STOCK CODE	PRICE (HK$)
SKE15A-05	9-18V	5V	645-242	226.00
SKE15A-12	9-18V	12V	645-243	226.00
SKE15A-15	9-18V	15V	645-244	226.00
SKE15A-24	9-18V	24V	645-245	226.00

DKE-15 Series

15W DC-DC 雙組輸出

15W DC-DC Dual Output

* Load regulation :±1%
* I/O isolation voltage : 1000 VDC (MIN.)
* I/O isolation resistance : 100MΩ(MIN.)



2" x 2" x 0.42"

MODEL	I/P	O/P	STOCK CODE	PRICE (HK$)
DKE15A-05	9-18V	±5V	645-254	266.00
DKE15A-12	9-18V	±12V	645-255	266.00
DKE15A-15	9-18V	±15V	645-256	266.00
DKE15A-24	9-18V	±24V	645-258	266.00

SDM-30-12S5

DC-DC 單組輸出

2:1 Wide Input Range DC-DC Regulated Output

* DC output: 5VDC, 5A
* DC input: 9~18VDC
* Built-in remote ON/OFF control, 1000VDC I/O isolation
* Protections: Short cirucit, over load, over voltage




STOCK CODE : 647-615 **PRICE : HK$ 300.00**

SDM-30-12S15

DC-DC 單組輸出

2:1 Wide Input Range DC-DC Regulated Output

* DC output: 15VDC, 1.7A
* DC input: 9~18VDC
* Built-in remote ON/OFF control, 1000VDC I/O isolation
* Protections: Short cirucit, over load, over voltage



STOCK CODE : 647-616 **PRICE : HK$ 300.00**

封裝型 Enclosed Type

SD-25 Series

25W單組輸出 DC-DC 轉換器

25W Single Output DC-DC Converter

* Load regulation :±0.5% MAX.
* Overload protection : 105%~150% fold back current limiting
* Withstand voltage : I/P-O/P: 1.5KV, I/P-FG: 1.5KV, O/P-FG: 0.5KV, 1 min.



CASE:905 99 x 97 x 35mm


MODEL	I/P	O/P	STOCK CODE	PRICE (HK$)
SD-25A-5	9.2-18V	5V	644-840	220.00
SD-25A-12	9.2-18V	12V	644-841	220.00
SD-25A-24	9.2-18V	24V	644-842	220.00
SD-25B-5	19-36V	5V	644-843	220.00

SD-50 Series

50W單組輸出 DC-DC 轉換器

50W Single Output DC-DC Converter

* Load regulation :±0.5% MAX.
* Overload protection : 105%~150% fold back current limiting
* Withstand voltage : I/P-O/P: 1.5KV, I/P-FG: 1.5KV, O/P-FG: 0.5KV, 1 min.



CASE:901 159 x 97 x 38mm

MODEL	I/P	O/P	STOCK CODE	PRICE (HK$)
SD-50A-5	9.2-18V	5V	644-849	278.00
SD-50A-12	9.2-18V	12V	644-850	278.00
SD-50A-24	9.2-18V	24V	644-851	278.00
SD-50B-5	19-36V	5V	644-852	278.00
SD-50B-12	19-36V	12V	644-853	278.00

SD-100 Series

100W單組輸出 DC-DC 轉換器

100W Single Output DC-DC Converter

* Load regulation :±0.5% MAX.
* Overload protection : 105%~135% fold back current limiting
* Withstand voltage : I/P-O/P: 1.5KV, I/P-FG: 1.5KV, O/P-FG: 0.5KV, 1 min.



CASE:902 199 x 98 x 38mm

MODEL	I/P	O/P	STOCK CODE	PRICE (HK$)
SD-100B-5	19-36V	5V	644-858	324.00
SD-100B-12	19-36V	12V	644-859	324.00
SD-100B-24	19-36V	24V	644-860	324.00
SD-100C-5	36-72V	5V	644-861	324.00

SD-150 Series

150W單組輸出 DC-DC 轉換器

150W Single Output DC-DC Converter

* Load regulation :±0.5% MAX.
* Overload protection : 105%~135% fold back current limiting
* Withstand voltage : I/P-O/P: 1.5KV, I/P-FG: 1.5KV, O/P-FG: 0.5KV, 1 min.



CASE:906 199 x 110 x 50mm

MODEL	I/P	O/P	STOCK CODE	PRICE (HK$)
SD-150B-12	19-36V	12V	644-867	472.00
SD-150B-24	19-36V	24V	644-868	472.00
SD-150C-12	36-72V	12V	644-869	472.00
SD-150C-24	36-72V	24V	644-870	472.00

SD-200B-24

5W單組輸出 DC-DC 轉換器

5W DC-DC Regulated Single Output

* 2:1 wide input range, 1500VDC I/O isolation
* Over load protection: 105~135%
* Output: 24VDC, 8.4A
* Input: 19~36VDC
* EMC standards: EN55022 class B



STOCK CODE : 647-634 **PRICE : HK$ 715.00**

封密型 Enclosed Type

MPS-120-12

醫學桌上型

Medical Desktop

* 30W AC-DC Single Output and Medical Type Safety & EMC
* 3 pole AC inlet IEC320-C14, fully enclosed plastic case
* Output: 18VDC, 1.67A
* Input: 90~264VAC, 135~370VDC
* Inrush Current: 35A / 235VAC



STOCK CODE : 647-633 **PRICE : HK$ 315.00**

Information in this document is subject to change without notice. Other products and companies referred to herein are trademarks or registered trademarks of their respective companies or mark holders.

封密型 Enclosed Type

MPS-120-12
醫學類型
Medical Type



* Medical safety approved, UL2601-1
* Output: 12VDC, 10A
* AC input: 90-264VAC, 127~370VDC
* AC inrush current: 35A at 115VAC, 60A at 230VAC
* Protections: Short cirucit, over load, over voltage

STOCK CODE : 647-614 **PRICE : HK$ 350.00**

分析儀 Analayzer

MFJ-259B
HF/VHF天線 / SWR/RF分析儀
HF / VHF Antenna / SWR / RF Analyzer



* Compact battery powered RF impedance analyzer
* Frequency range of impedance measurement is 1.8 - 170 MHz in six overlapping banks
* Good fit for analyzing 50 ohm anteena and transmission line systems
* Highly accurate measurement: Using Microwave zero-bias Schottky detectors
* Used to adjust, test or measure the following: Antennas, Antenna tuners, Amplifiers, Coaxial transmission lines, Filters, Matching or tuning stubs, Traps, Tuned Circuits, Small Cpapcitors, RF Chokes and Inductors, Oscillators Frequency

STOCK CODE : 646-029 **PRICE : HK$ 2,400.00**





500系列數字式卡尺 Series 500 Digimatic Calipers With Absolute Encoder — Mitutoyo

500-151
數字量式卡尺
Digimatic Calipers



* Range : 0 - 150mm
* LCD resolution : 0.01mm
* Accuracy : ±0.02mm
* With SPC output
* Remember its measuring position even after the gage has been switched off

STOCK CODE : 218-321 **PRICE : HK$ 1,140.00**

500-172
數字量式卡尺
Digimatic Calipers



* Range : 0 - 8" ; 0 - 200mm
* LCD resolution : 0.0005" ; 0.01mm
* Accuracy : ±0.001"
* With SPC output
* Remember its measuring position even after the gage has been switched off

STOCK CODE : 218-318 **PRICE : HK$ 1,470.00**

500-173
數字量式卡尺
Digimatic Calipers



* Range : 0 - 12" ; 0 - 300mm
* LCD resolution : 0.0005" ; 0.01mm
* Accuracy : ±0.0015"
* With SPC output
* Remember its measuring position even after the gage has been switched off

STOCK CODE : 218-319 **PRICE : HK$ 2,530.00**

500-505-10
數字量式卡尺
Digimatic Calipers



* Range : 0 - 18" ; 0 - 450mm
* LCD resolution : 0.0005" ; 0.01mm
* Accuracy : ±0.002"
* With SPC output, without Depth Bar Absolute Function Type
* Remember its measuring position even after the gage has been switched off

STOCK CODE : 218-320 **PRICE : HK$ 5,020.00**

573系列數字量式卡尺 Series 573 Digimatic Inside Calipers With Absolute Encorder — Mitutoyo

573-146-10
數字量式卡尺
Digimatic Inside Calipers



* Range : 20 - 150mm
* Accuracy : ±0.03mm
* Pointed jaw type, with SPC output. Without Depth Bar
* Specially designed for inside measurements in hard to reach places
* All Digimatic models incorporate Mitutoyo's exclusive Absolute reading scale
* The Absolute scale always knows its true position from the origin point and never needs zero-setting

STOCK CODE : 218-327 **PRICE : HK$ 4,500.00**

573-242-10
數字量式卡尺
Digimatic Inside Calipers



* Range : 0.4 - 8" ; 10.16 - 200mm
* Accuracy : ±0.02"
* Knife-edge type, with SPC output. Without Depth Bar
* Specially designed for inside measurements in hard to reach places
* All Digimatic models incorporate Mitutoyo's exclusive Absolute reading scale
* The Absolute scale always knows its true position from the origin point and never needs zero-setting

STOCK CODE : 218-324 **PRICE : HK$ 4,770.00**

573系列數字量式卡尺 Series 573 Digimatic Inside Calipers With Absolute Encorder — Mitutoyo

573-245-10
數字量式卡尺
Digimatic Inside Calipers



* Range : 0.4 - 6" ; 10.16 - 150mm
* Accuracy : ±0.02"
* Inside groove type, with SPC output. Without Depth Bar
* Specially designed for inside measurements in hard to reach places
* All Digimatic models incorporate Mitutoyo's exclusive Absolute reading scale
* The Absolute scale always knows its true position from the origin point and never needs zero-setting

STOCK CODE : 218-325 **PRICE : HK$ 3,790.00**

573-246-10
數字量式卡尺
Digimatic Inside Calipers



* Range : 0.8 - 6" ; 20.32 - 150mm
* Accuracy : ±0.015"
* Pointed jaw type, with SPC output. Without Depth Bar
* Specially designed for inside measurements in hard to reach places
* All Digimatic models incorporate Mitutoyo's exclusive Absolute reading scale
* The Absolute scale always knows its true position from the origin point and never needs zero-setting

STOCK CODE : 218-326 **PRICE : HK$ 4,530.00**

測微計 Series 293 Digimatic Micrometer — Mitutoyo

293-230
測微計
Digimatic Micrometer



* Range : 0 - 25mm
* Accuracy : ±0.001mm
* With SPC output and ratchet stop
* Two measuring modes-ABS (absolute) and INC (incremental) - for efficient measurement (with SPC output Model)
* Functions available : Origin setting, Inch/mm selection, Zero-setting, Data Hold only with SPC Models, Error alarm, Auto-sleep, Data output

STOCK CODE : 218-460 **PRICE : HK$ 1,640.00**

293-231
測微計
Digimatic Micrometer



* Range : 25 - 50mm
* Accuracy : ±0.001mm
* With SPC output and standard ratchet stop
* Two measuring modes-ABS (absolute) and INC (incremental) - for efficient measurement (with SPC output Model)
* Functions available : Origin setting, Inch/mm selection, Zero-setting, Data Hold only with SPC Models, Error alarm, Auto-sleep, Data output

STOCK CODE : 218-461 **PRICE : HK$ 1,780.00**

293-232
測微計
Digimatic Micrometer



* Range : 50 - 75mm
* Accuracy : ±0.001mm
* With SPC output and standard ratchet stop
* Two measuring modes-ABS (absolute) and INC (incremental) - for efficient measurement (with SPC output Model)
* Functions available : Origin setting, Inch/mm selection, Zero-setting, Data Hold only with SPC Models, Error alarm, Auto-sleep, Data output

STOCK CODE : 218-462 **PRICE : HK$ 2,130.00**

293-331
測微計
Digimatic Micrometer



* Range : 1 - 2" ; 25.4 - 50.8mm
* Accuracy : ±0.0005"
* With SPC output and standard ratchet stop
* Two measuring modes-ABS (absolute) and INC (incremental) - for efficient measurement (with SPC output Model)
* Functions available : Origin setting, Inch/mm selection, Zero-setting, Data Hold only with SPC Models, Error alarm, Auto-sleep, Data output

STOCK CODE : 218-457 **PRICE : HK$ 1,780.00**

Information in this document is subject to change without notice. Other products and companies referred to herein are trademarks or registered trademarks of their respective companies or mark holders.