

測試用導線

Testing Leads and Accessories

MISCELLANEOUS

KLG-2, KLG-4, KLN-4 Series

拼體測試導線

Stackable Test Leads

- * 2 / 4 mm Plug with cage springs, 4mm socket in parallel of various length
- * Stackable with each other
- * Contact surface nickel or gold plated with reference voltage 50V
- * Current Rating : 10A for 2mm and 19A for 4mm plug
- * Connecting Wire : AWG 20
- * KLG-2-15/H : 2mm Plug with 15mm wire
- * KLG-2-30/H : 2mm Plug with 30mm wire
- * KLG-2-45/H : 2mm Plug with 45mm wire
- * KLG-2-60/H : 2mm Plug with 60mm wire
- * KLG-4-25/H : 4mm Plug with 25mm wire
- * KLG-4-50/H : 4mm Plug with 50mm wire
- * KLG-4-75/H : 4mm Plug with 75mm wire
- * KLG-4-100/H : 4mm Plug with 100mm wire
- * KLN-4-25/H : 4mm Plug with 25mm wire
- * KLN-4-75/H : 4mm Plug with 75mm wire
- * KLN-4-100/H : 4mm Plug with 100mm wire



MODEL	STOCK CODE	PRICE (HK\$)
KLG-2-15/H	635-141	168.00
KLG-2-30/H	635-142	175.00
KLG-2-45/H	635-143	168.00
KLG-2-60/H	635-144	192.00
KLG-4-25/H	635-149	140.00
KLG-4-50/H	635-150	145.00
KLG-4-75/H	635-151	150.00
KLG-4-100/H	635-152	155.00
KLN-4-25/H	635-153	107.00
KLN-4-75/H	635-154	115.00
KLN-4-100/H	635-155	118.00

KTN-2, KTN-4 Series

測試及連接用套件

Test & Connecting Lead Sets

- * Different 1 M long PVC test lead fitted at one end with a test probe with the other end either fitted with stackable plug, normal plug or shrouded plug
- * Size of the plug varies from 3mm to 4mm
- * Working voltage max 250VAC, maximum current rating 10A
- * Suitable for use with all equipment with 2mm or 4mm socket
- * KTN-2-AA/H : 2mm plug with test lead
- * KTN-2-BA/H : Shoulded 2mm Plug with test lead
- * KTN-2-CA/H : Stackable 2mm Plug with test lead
- * KTN-4-AA/H : 4mm Plug with test lead
- * KTN-4-BA/H : Shoulded 4mm Plug with test lead
- * KTN-4-CA/H : Stackable 4mm Plug with test lead



MODEL	STOCK CODE	PRICE (HK\$)
KTN-2-AA/H	635-164	30.00
KTN-2-BA/H	635-165	30.00
KTN-2-CA/H	635-166	35.00
KTN-4-AA/H	635-167	40.00
KTN-4-BA/H	635-168	40.00
KTN-4-CA/H	635-169	42.00

BDG, HBP Series

接線柱

Binding Posts

- * Various size binding post made of steel with plastic body
- * Addition hole inside the body provided for stackable plug or wire insertion
- * Available in 2 different size 4mm, 6mm and 3 color, BLUE, BLACK, RED
- * BDG-P04C2 : Binding post, 4mm, Red
- * BDG-P04C4 : Binding post, 4mm Blue
- * BDG-P04C9 : Binding post, 4mm Black
- * HBP-002-Black : Binding post, 5mm, Black
- * HBP-002-Red : Binding post, 5mm, Red



MODEL	STOCK CODE	PRICE (HK\$)
BDG-P04C2	631-074	5.00
BDG-P04C4	631-075	5.00
BDG-P04C9	631-076	5.00
HBP-002-Black	631-054	6.00
HBP-002-Red	631-055	6.00

測試用導線

Testing Leads and Accessories

MISCELLANEOUS

BAN, HPM Series

香蕉插

Banana Plug

- * Range of Nickel plated plug with spring like plate construction to ensure adapt contact with 4mm sockets
- * Connection wire could be solder or screwed into the plug
- * Available in 2 color and two quality
- * BAN-P04C2 : Banana Plug, Red
- * BAN-P04C9 : Banana Plug, Black
- * HPM610-B : Banana Plug, Low cost, Black
- * HPM601-R : Banana Plug, Low cost, Red



MODEL	STOCK CODE	PRICE (HK\$)
BAN-P04C2	631-011	5.00
BAN-P04C9	631-012	5.00
HPM610-B	631-058	3.00
HPM601-R	631-059	3.00

HPM-00X Series

3.5mm 電話插

3.5mm Phone Plug

- * Available in mono & stereo
- * HPM-005 : Mono Plug
- * HPM-006 : Stereo Plug, Black
- * HPM-008 : Stereo Plug with cable protector



MODEL	STOCK CODE	PRICE (HK\$)
HPM-005	631-048	2.00
HPM-006	631-056	2.00
HPM-008	631-057	4.00

HPM-01X Series

6.3mm 立體聲電話插

6.3mm Stereo Phone Plug

- * HPM-011 : Stereo Plug
- * HPM-012 : Stereo Plug with Cable Preprotector



MODEL	STOCK CODE	PRICE (HK\$)
HPM-011	631-062	3.00
HPM-012	631-304	5.00

彈簧試驗接觸探針

Spring Test Contact Probe

MISCELLANEOUS

- * Spring test contact probe is an electro-mechanical component consisting of a tubular housing battel containing a compression spring, ball and plunger
- * Contact probe are developed specially to meet stringent electrical / electronics testing requirements in a variety of applications like PCB Open / Short testing, functional testing and automatic In-Circuit Testing

PLUNGER	TOP STYLE	PLUNGER	TOP STYLE
4-Wire	2-Wire	4-Wire	2-Wire
4-Wire	2-Wire	4-Wire	2-Wire
4-Wire	2-Wire	4-Wire	2-Wire
4-Wire	2-Wire	4-Wire	2-Wire
4-Wire	2-Wire	4-Wire	2-Wire
4-Wire	2-Wire	4-Wire	2-Wire
4-Wire	2-Wire	4-Wire	2-Wire
4-Wire	2-Wire	4-Wire	2-Wire
4-Wire	2-Wire	4-Wire	2-Wire

SOB30

50 密爾(千分之一英寸)測試探針 (適用於SMD)

50mil Test Probe (Suitable for SMD use)

- * Current Rating : 3 Amp ; Material : Rhodium
- * Contact Resistance : 50 mΩ ; Spring Force : 4 oz.
- * Working Travel : 1.78 mm ; Probe Diameter : 0.69 mm
- * SOB30 : Spare
- * SOT45 : Slide Chisel
- * SOUT : Tapered Crown Housing Type
- * ROSC : Solder Clip

MODEL	STOCK CODE	PRICE (HK\$)
SOB30	621-010	130.00
SOT45	621-011	130.00
SOUT	621-012	130.00
ROSC	621-015	50.00

彈簧試驗接觸探針

Spring Test Contact Probe

MISCELLANEOUS

S2B30-4G

100 密爾測試探針, 4 盎司(適用於JIG)

100mil Test Probe, 4 oz (Suitable for JIG use)

- * Current Rating : 3 Amp ; Material : Rhodium
- * Contact Resistance : 50 mΩ ; Spring Force : 4 oz.
- * Working Travel : 2.54 mm ; Probe Diameter : 1.37 mm
- * S2B30-4G : Spare
- * S2V-4G : Crown, 0.06
- * S2H-4G : Serrated
- * S2Y-4G : Tulip Receptacle Type
- * R2SC : Solder Clip

MODEL	STOCK CODE	PRICE (HK\$)
S2B30-4G	621-020	80.00
S2V-4G	621-021	80.00
S2H-4G	621-022	80.00
S2Y-4G	621-023	65.00
R2SC	621-025	50.00

S25, R25 Series

100 密爾測試探針, 7 盎司(適用於JIG)

100mil Test Probe, 7 oz (Suitable for JIG use)

- * Current Rating : 3 Amp ; Material : Rhodium
- * Contact Resistance : 50 mΩ ; Spring Force : 7 oz.
- * Working Travel : 4.32 mm ; Probe Diameter : 1.37 mm
- * S25B30-4G : Spare
- * S25W-4G : Crown, 0.05
- * S25H-4G : Serrated
- * S25Y-4G : Tapered Crown Receptacle Type
- * R25SC : Solder Clip
- * R25WW : Wirewrap

MODEL	STOCK CODE	PRICE (HK\$)
S25B30-4G	621-030	80.00
S25W-4G	621-031	80.00
S25H-4G	621-032	80.00
S25Y-4G	621-033	80.00
R25SC	621-035	40.00
R25WW	621-036	40.00

Typical Applications



安全性手電筒

Handlamp

WOLFLITE

H-251A

安全性手電筒

Safety Handlamp

- * The battery is Intrinsically Safe by fast switching short-circuit protection circuit
- * Lloyd's Register Type approved
- * Explosive gas, vapour and mist certified for zones 1 & 2, up to T4 temperature class
- * Lens made from 6mm toughened glass
- * Withstand the drop and impact expected from heavy industrial use
- * Long life halogen bulb, focused within a 100mm diameter parabolic reflector giving an extremely well defined beam of intense white light
- * Battery Charger is not included



STOCK CODE : 647-308 PRICE : HK\$ 2,976.00



We welcome your comments on our products & services