

DIP 插座  
DIP Sockets & Receptacles

## DIP Receptacles

0.100" DIP 插座

.100" DIP Receptacles

- \* Solder Tail, .13 in. (3.3 mm) Contact Tail
- \* Wire Wrap, .62 in. (15.7 mm) Contact Tail

| MODEL             | STOCK CODE | PRICE (HK\$) |
|-------------------|------------|--------------|
| 214-3339-19-0602J | 666-203    | 85.00        |
| 218-3594-19-0602  | 666-109    | 105.00       |
| 220-3595-00-0602  | 666-158    | 250.00       |
| 224-3597-00-0602  | 666-184    | 160.00       |
| 232-1285-19-0602  | 666-160    | 110.00       |



## Universal ZIP DIP Sockets

0.100" DIP 插座

.100" DIP Sockets

- Universal ZIP DIP Socket is for DIPs with .100 in. lead spacing and has an extra wide contact zone which allows insertion of DIPs with distance between rows from .300 in. through .600 in.

| MODEL             | STOCK CODE | PRICE (HK\$) |
|-------------------|------------|--------------|
| 228-6023-00-0605  | 666-016    | 118.00       |
| 232-7282-00-0602  | 666-193    | 120.00       |
| 240-1288-00-0602J | 666-171    | 135.00       |



## ZIP DIP Sockets

0.100" DIP 插座

.100" DIP Sockets

- \* For DIPs with .100" lead spacing
- \* Pin counts for 14-64 leads
- \* Lever actuated zero insertion force mechanism
- \* Socket easily disassembles for repairability
- \* Socket contact point of .110" below top surface of socket

| MODEL             | STOCK CODE | PRICE (HK\$) |
|-------------------|------------|--------------|
| 214-3339-00-0602J | 666-191    | 80.00        |
| 216-3340-00-0602J | 666-176    | 85.00        |
| 220-3342-00-0602J | 666-199    | 115.00       |
| 222-3343-00-0602J | 666-005    | 75.00        |
| 224-1275-00-0602J | 666-007    | 75.00        |
| 232-1285-00-0602J | 666-125    | 90.00        |
| 240-1280-00-0602J | 666-094    | 88.00        |
| 264-4493-00-0602J | 666-248    | 190.00       |



## Shrink DIP

0.070" DIP 插座

.070" DIP Socket

- \* Shrink ZIP DIP Socket is for DIPs with .07 in. lead spacing and accommodates pin counts from 28 through 90 leads
- \* The socket has a contact point of .09 in. below top surface of socket and is designed with a lever actuated zero insertion force mechanism

| MODEL             | STOCK CODE | PRICE (HK\$) |
|-------------------|------------|--------------|
| 242-1293-00-0602J | 666-228    | 140.00       |
| 264-1300-00-0602J | 666-022    | 300.00       |



## SOIC Sockets

測試及老化 SOIC 插座

Test &amp; Burn-In SOIC Sockets

- \* Flip top lid can be actuated from top or front and springs open when unlatched
- \* Compact envelope and side to side stackability maximize board density
- \* Tweezer slot for easy manual loading/unloading

| MODEL            | STOCK CODE | PRICE (HK\$) |
|------------------|------------|--------------|
| 208-7391-55-1902 | 666-142    | 130.00       |
| 214-7390-55-1902 | 666-144    | 205.00       |
| 216-7224-55-1902 | 666-143    | 150.00       |
| 218-7223-55-1902 | 666-130    | 255.00       |
| 220-7201-55-1902 | 666-135    | 245.00       |
| 228-7396-55-1902 | 666-202    | 295.00       |



## Strip Sockets

0.100" 單行線 ZIP 插座

.100" In-Line ZIP Strip Sockets

- \* For single-in-line packages on .100" centers
- \* SIP pin counts from 10 through 36 leads
- \* Can be used in sets of two or more to create a socket for non-standard leaded packages on .100" centers

| MODEL            | STOCK CODE | PRICE (HK\$) |
|------------------|------------|--------------|
| 210-2599-00-0602 | 666-025    | 165.00       |
| 220-2600-00-0602 | 666-026    | 165.00       |
| 232-2601-00-0602 | 666-205    | 340.00       |

DIP 插座  
DIP Sockets & Receptacles

## Staggered ZIP Strip Sockets

0.050" x 0.100" 排體式 ZIP 插座

.050" x .100" Staggered ZIP

Strip Sockets

- \* For devices with .050" lead centers formed in staggered rows with .100" between centers and rows
- \* Socket with top-plate cover required vertical insertion of leads

| MODEL            | STOCK CODE | PRICE (HK\$) |
|------------------|------------|--------------|
| 232-1270-01-0602 | 666-033    | 400.00       |
| 239-5605-01-0602 | 666-052    | 180.00       |



## ZIP Strip Axial In-Line Sockets

0.100" 核心

.100" Centers

- \* For single-in-line packages on .100" lead centers, unformed or extending axially from package
- \* Socket contact extend above socket body and enable horizontal insertion of leads

| MODEL            | STOCK CODE | PRICE (HK\$) |
|------------------|------------|--------------|
| 210-3548-00-0602 | 666-194    | 190.00       |
| 220-3549-00-0602 | 666-030    | 530.00       |



## ZIP Strip Axial Lead Sockets

0.050" x 0.100" 軸向接腳插座

.050" x .100" Axial Lead Sockets

- \* For devices with .050" lead centers unformed or extending axially from package
- \* Socket without top-plate cover enables horizontal insertion of leads

| MODEL            | STOCK CODE | PRICE (HK\$) |
|------------------|------------|--------------|
| 234-3034-01-0602 | 666-209    | 319.00       |
| 234-3034-02-0602 | 666-210    | 258.00       |
| 235-3019-01-0602 | 666-200    | 345.00       |
| 251-5949-01-0602 | 666-045    | 430.00       |
| 251-5949-02-0602 | 666-048    | 430.00       |



## PLCC Sockets

SOJ 系列

SOJ Series

- \* Lidded style socket assures consistent normal force on PLCC leads for maximum electrical reliability
- \* Solid lid with fixed foot height controls deflection
- \* Compliant leads accommodate package planarity variations
- \* Alignment ribs fit between J-leads to assure proper registration

| MODEL            | STOCK CODE | PRICE (HK\$) |
|------------------|------------|--------------|
| 218-6218-51-1102 | 666-132    | 300.00       |
| 232-2601-00-0602 | 666-205    | 340.00       |

模子壓製加工製造  
Assembly Press

3M-3640

壓製 3M 電子電纜連接器

Assembly Of 3M Electronic Connectors

- \* Press unit can be mounted on bench or table
- \* 17:1 mechanical crimping action to reduce operator fatigue
- \* An over center handle design, weight: 3.9 Kg
- \* Size(LxWxH): 0.343x0.318x0.257 meter



STOCK CODE : 665-007

PRICE : HK\$ 4,750.00

鱷魚夾  
Alligator Clip

## Pomona MG-B

小型鱷魚夾軟線

Miniature Alligator Clip Patch Cord

- \* Features flex boots for insulation protection
- \* Alligators are nickel plated for tarnish resistance
- \* Alligators clip has .187" (4.75mm) max. jaw opening
- \* Ideal for use as a temporary wire



| MODEL                | STOCK CODE | PRICE (HK\$) |
|----------------------|------------|--------------|
| POMONA MG-B-4-0 4"   | 668-162    | 39.00        |
| POMONA MG-B-8-0 8"   | 668-457    | 39.00        |
| POMONA MG-B-12-0 12" | 668-458    | 39.00        |
| POMONA MG-B-24-0 24" | 668-459    | 39.00        |
| POMONA MG-B-36-0 36" | 668-460    | 39.00        |
| POMONA MG-B-48-0 48" | 668-461    | 43.00        |
| POMONA MG-B-60-0 60" | 668-462    | 43.00        |

香蕉插  
Banana Plug

## Pomona 2484

排體式香蕉插連伸縮捲圈線

Stacking Banana Plug Each End

On Retractable (Coiled) Cord

- \* Cross stacking and vertical stacking on both ends
- \* Mates to model #1581, 2854 or any standard banana jack
- \* 20 AWG Wire, .087 O.D., Extended Length : 48"
- \* RATING : 270 VDC duty, 5 Amps, +55 °C (+131 °F) Max.
- \* STD COLORS : -0 blk, -2 red



| MODEL         | STOCK CODE | PRICE (HK\$) |
|---------------|------------|--------------|
| POMONA 2484-0 | 668-129    | 92.00        |

## Pomona 2948

鍍金排體式香蕉插連軟線

Stacking Banana Plug Patch

Cord, Gold-Plated

- \* Multiple stacking feature accommodates the most complex stacking; keeps circuitry neater
- \* Greatly simplifies circuit connections and changes
- \* Reliable solder bonded connections withstand pull test in excess of 50 lbs
- \* Vertical and cross stackable

| MODEL                | STOCK CODE | PRICE (HK\$) |
|----------------------|------------|--------------|
| POMONA 2948-12-0 12" | 668-126    | 59.00        |
| POMONA 2948-24-0 24" | 668-486    | 59.00        |
| POMONA 2948-36-0 36" | 668-487    | 59.00        |
| POMONA 2948-48-0 48" | 668-488    | 61.00        |
| POMONA 2948-60-0 60" | 668-489    | 61.00        |



## Pomona 4702

香蕉插頭轉香蕉插座

Banana Plug To Banana Jack

- \* Dual Purpose
- \* Insulates all hot leads when used as an extension cord
- \* Endless extension couplings possible with any banana plug patch cord



| MODEL                | STOCK CODE | PRICE (HK\$) |
|----------------------|------------|--------------|
| POMONA 4702-24-0 24" | 668-431    | 46.00        |
| POMONA 4702-36-0 36" | 668-432    | 46.00        |
| POMONA 4702-48-0 48" | 668-433    | 48.00        |
| POMONA 4702-60-0 60" | 668-434    | 48.00        |

## Pomona 4771

香蕉插轉 0.025 方形插座

Banana Plug To .025 Square

Receptacle

- \* This patch cord is excellent for use as a jumper on circuit cards with 0.6 (.025) sq. pins and equipment with 4.2 (.166) dia. pin jacks
- \* Mates to Model numbers 5790, 4521, 5360 and 5927



| MODEL                | STOCK CODE | PRICE (HK\$) |
|----------------------|------------|--------------|
| POMONA 4771-24-0 24" | 668-416    | 42.00        |
| POMONA 4771-36-0 36" | 668-417    | 42.00        |
| POMONA 4771-48-0 48" | 668-418    | 42.00        |

## 香蕉插

## Banana Plug

Pomona®

## Pomona HB

水平拼體式香蕉插連線  
Horizontal Stacking Banana Plug  
Patch Cord

- \* Front and vertical stacking banana plug
- \* Mates to standard banana jacks
- \* Ideal for providing jumpers on chassis boxes



| MODEL          | STOCK CODE  | PRICE (HK\$) |
|----------------|-------------|--------------|
| POMONA HB-12-0 | 12" 668-128 | 59.00        |
| POMONA HB-24-0 | 24" 668-495 | 59.00        |
| POMONA HB-36-0 | 36" 668-496 | 59.00        |
| POMONA HB-48-0 | 48" 668-497 | 63.00        |
| POMONA HB-60-0 | 60" 668-498 | 63.00        |

## 香蕉插頭轉測試鉤軟線

## Banana Plug to Grabber Test Clip

Pomona®

## Pomona 3782

測試鉤及拼體式香蕉插頭  
Minigrabber Test Clip To Stacking  
Banana Plug

- \* Provides a Minigrabber output from a Banana Jack
- \* Banana plug is capable of vertical and cross stacking
- \* Mates to Model 1581 or any standard Banana Jack



| MODEL            | STOCK CODE  | PRICE (HK\$) |
|------------------|-------------|--------------|
| POMONA 3782-12-0 | 12" 668-501 | 32.00        |
| POMONA 3782-24-0 | 24" 668-135 | 32.00        |
| POMONA 3782-36-0 | 36" 668-502 | 32.00        |
| POMONA 3782-48-0 | 48" 668-503 | 34.00        |
| POMONA 3782-60-0 | 60" 668-504 | 34.00        |

## Pomona 3784

測試鉤及袖珍型香蕉插頭  
Minigrabber Test Clip To Mini  
Banana Plug

- \* Provides a Minigrabber output from a miniature Banana Jack
- \* Mates to Model #2192 or any miniature Banana Jack
- \* Miniature Banana plug is vertically stackable



| MODEL            | STOCK CODE  | PRICE (HK\$) |
|------------------|-------------|--------------|
| POMONA 3784-24-0 | 24" 668-190 | 38.00        |
| POMONA 3784-36-0 | 36" 668-439 | 38.00        |

## Pomona 4650

測試鉤至筆直型香蕉插頭  
Minigrabber Test Clip To Straight  
Banana Plug

- \* Ideal for connecting terminals and wire wrap post to test equipment
- \* Banana Plug mates to Model #4702, 1581 or any standard Banana Jack



| MODEL            | STOCK CODE  | PRICE (HK\$) |
|------------------|-------------|--------------|
| POMONA 4650-24-0 | 24" 668-477 | 43.00        |
| POMONA 4650-36-0 | 36" 668-478 | 43.00        |

## Pomona 6249

測試鉤至多拼體式香蕉插頭  
Minigrabber Test Clip To Multi  
Stacking Banana Plug

- \* Newly designed Minigrabber Test Clip Patch Cord offers a high 300 Volt and 5 amp rating
- \* Grabber width is a slim .36" (9.14 mm) for easier access to test terminals
- \* Plug is molded directly to the cable in an integral one-piece design for a long lasting connection



| MODEL            | STOCK CODE  | PRICE (HK\$) |
|------------------|-------------|--------------|
| POMONA 6249-12-0 | 12" 668-134 | 37.00        |
| POMONA 6249-24-0 | 24" 668-499 | 37.00        |
| POMONA 6249-36-0 | 36" 668-500 | 40.00        |

## 香蕉插頭轉測試鉤軟線

## Banana Plug to Grabber Test Clip

Pomona®

## Pomona 6298

測試鉤至拼體式香蕉插頭  
Minipincer Test Clip To Stacking  
Banana Plug

- \* Pincer patch cord interfaces directly into the most popular multimeters configured with non-sheathed style banana jacks
- \* Plug is molded directly to the cable in an integral one-piece design for a long lasting connection
- \* Banana plug features top and side stacking for added test versatility



| MODEL            | STOCK CODE  | PRICE (HK\$) |
|------------------|-------------|--------------|
| POMONA 6298-12-0 | 12" 668-142 | 51.00        |
| POMONA 6298-24-0 | 24" 668-505 | 51.00        |
| POMONA 6298-36-0 | 36" 668-506 | 51.00        |

## 觸針電纜軟線

## Pin Tip Plug

Pomona®

## Pomona P

觸針電纜軟線  
Pin Tip Plug Patch Cord

- \* Stackable pin tip plugs
- \* Ideal for use as jumper wires on chassis boxes
- \* Mates to Model #3542, 4773 or any other standard .08 inch pin jack



| MODEL         | STOCK CODE  | PRICE (HK\$) |
|---------------|-------------|--------------|
| POMONA P-4-0  | 4" 668-186  | 41.00        |
| POMONA P-8-0  | 8" 668-423  | 41.00        |
| POMONA P-12-0 | 12" 668-424 | 41.00        |
| POMONA P-18-0 | 18" 668-425 | 41.00        |
| POMONA P-24-0 | 24" 668-426 | 41.00        |
| POMONA P-36-0 | 36" 668-427 | 41.00        |
| POMONA P-48-0 | 48" 668-428 | 44.00        |
| POMONA P-60-0 | 60" 668-429 | 44.00        |

## 鑷型端子

## Spade Lug

Pomona®

## Pomona 1693

鑷型端子配線供低電壓測量  
Spade Lug Patch Cord For Low  
Voltage Measurements

- \* The Model 1693 is part of a family of test accessories ideal for low voltage precision measurements
- \* Spade lugs of high conductivity gold plated ETP copper alloy 110, are attached to low resistance multi-stranded 12 gauge wire



| MODEL            | STOCK CODE  | PRICE (HK\$) |
|------------------|-------------|--------------|
| POMONA 1693-36-0 | 36" 668-123 | 138.00       |
| POMONA 1693-60-0 | 60" 668-411 | 138.00       |

## Pomona 1756

低電壓鑷型端子配線  
Shielded Low Voltage Spade Lug  
Patch Cord

- \* Pomona's Model 1756 is part of a family of test accessories ideal for low voltage precision measurements
- \* Spade lugs are of high conductivity, gold plated ETP copper alloy 110, to greatly minimize the effect of Thermal Electric Voltage (Thermal EMF)



| MODEL          | STOCK CODE  | PRICE (HK\$) |
|----------------|-------------|--------------|
| POMONA 1756-24 | 24" 668-321 | 338.00       |
| POMONA 1756-48 | 48" 668-122 | 338.00       |

## 微型鉤電纜配線

## Grabber Patch Cords

Pomona®

## Pomona 3780

袖珍型測試鉤 (只提供1端)  
Minigrabber Test Clip One End Only

- \* Minigrabber Test Clip (one end only) allows customization of the open end
- \* Grabber attaches to terminals sizes up to .060" (1.5mm)
- \* For added safety, the grabber body material is fire retardant Nylon 6
- \* Stainless steel grabber compression spring resists corrosion and retains a firm feel throughout the life of the grabber



| MODEL            | STOCK CODE  | PRICE (HK\$) |
|------------------|-------------|--------------|
| POMONA 3780-60-0 | 60" 668-148 | 25.00        |

## 微型鉤電纜配線

## Grabber Patch Cords

Pomona®

## Pomona 3781

袖珍型測試鉤電纜配線  
Minigrabber Test Clip Patch Cord

- \* Ideal for providing temporary jumper wires
- \* Provides excellent connector to terminals and wire wrap posts



| MODEL            | STOCK CODE  | PRICE (HK\$) |
|------------------|-------------|--------------|
| POMONA 3781-8-0  | 8" 668-401  | 32.00        |
| POMONA 3781-12-0 | 12" 668-405 | 32.00        |
| POMONA 3781-18-0 | 18" 668-450 | 32.00        |
| POMONA 3781-24-0 | 24" 668-147 | 32.00        |
| POMONA 3781-36-0 | 36" 668-451 | 32.00        |
| POMONA 3781-48-0 | 48" 668-452 | 34.00        |
| POMONA 3781-60-0 | 60" 668-453 | 34.00        |

## Pomona 5301

SMD 測試鉤電纜配線

SMD Grabber Test Clip Patch Cord

- \* Ideal for providing a temporary jumper wire between surface mount devices
- \* Pincer opens to .040
- \* 22 AWG Wire, .064 O.D.
- \* RATING: 150 V, 0.5 Amps, +102 °C (+216 °F) Max.
- \* STD COLORS: -0 blk, -2 red



| MODEL            | STOCK CODE  | PRICE (HK\$) |
|------------------|-------------|--------------|
| POMONA 5301-6-0  | 6" 668-154  | 53.00        |
| POMONA 5301-12-0 | 12" 668-454 | 53.00        |
| POMONA 5301-24-0 | 24" 668-455 | 53.00        |
| POMONA 5301-36-0 | 36" 668-456 | 53.00        |

## Pomona 5412

SMD 測試鉤連 0.025" 插座配線

SMD Grabber Test Clip To

.025" sq. Receptacle Patch Cord

- \* SMD Grabber Test Clip features gold plated stainless steel pincer for durability and low contact resistance
- \* Ideal for jumping to .025" (64mm) square pins
- \* Receptacle is gold plated to optimize the electrical connection



| MODEL            | STOCK CODE  | PRICE (HK\$) |
|------------------|-------------|--------------|
| POMONA 5412-12-0 | 12" 668-184 | 52.00        |
| POMONA 5412-24-0 | 24" 668-419 | 52.00        |
| POMONA 5412-36-0 | 36" 668-420 | 52.00        |

## Pomona 5521

SMD 微型鉤配線套件

SMD Grabber Test Clip Patch Cord Kit

- \* Ideal for providing a temporary jumper wire between surface mount devices
- \* Kit contains 10 pcs. of Model 5301-24, one of ten colors



STOCK CODE: 668-155 PRICE: HK\$ 489.00

## Pomona 5523

微型鉤配線套件

Minigrabber Test Clip Patch Cord Kit

- \* Ideal for providing temporary jumper wires
- \* Provides excellent connector to terminals and wire wrap posts



STOCK CODE: 668-408 PRICE: HK\$ 279.00

## Pomona 5924

SMD 測試鉤連 0.025" 插座配線

SMD Grabber Test Clip To

- \* .025" sq. Receptacle Kit
- \* SMD Grabber Test Clip features gold plated stainless steel pincer for durability and low contact resistance
- \* Ideal for jumping to .025" (64mm) square pins
- \* Receptacle is gold plated to optimize the electrical connection



STOCK CODE: 668-197 PRICE: HK\$ 453.00

### 微型鉤電纜配線 Grabber Patch Cords

#### Pomona 6246

##### 袖珍型微型鉤電纜配線

##### Minigrabber Test Clip Patch Cord

- \* Newly designed Minigrabber Test Clip Patch Cord offers a high 300 Volt and 5 amp rating
- \* Grabber width is a slim .36" (9,14 mm) for easier access to test terminals
- \* High strand count silicone insulated wire offers excellent flexibility and high temperature resistance



| MODEL            | STOCK CODE | PRICE (HK\$) |
|------------------|------------|--------------|
| POMONA 6246-12-0 | 668-145    | 37.00        |
| POMONA 6246-24-0 | 668-446    | 37.00        |
| POMONA 6246-36-0 | 668-447    | 37.00        |

#### Pomona 6247

##### 微型鉤電纜配線 (1端開放型)

##### Minigrabber Test Clip, One End Only

- \* Newly designed Minigrabber Test Clip Patch Cord offers a high 1,000 Volt and 5 amp rating
- \* Grabber width is a slim .36" (9,14 mm) for easier access to test terminals
- \* High strand count silicone insulated wire offers excellent flexibility and high temperature resistance



| MODEL            | STOCK CODE | PRICE (HK\$) |
|------------------|------------|--------------|
| POMONA 6247-48-0 | 668-146    | 30.00        |

### 微型測試鉤 Grabber Test Clips

#### Pomona 3925

##### 袖珍微型測試鉤

##### Minigrabber Test Clip

- \* Insulation : Glass filled nylon
- \* Marking : "Pomona 3925"
- \* Hand-held testing : 30VAC/60VDC Max.
- \* Minigrabber test clip for max. .090 wire dia, Do-It-Yourself
- \* Body : Contact - Gold Plated Beryllium Copper, Spring - Stainless Steel
- \* Hands free testing in controlled voltage environments : 300 WVDC Max.



| MODEL                | STOCK CODE | PRICE (HK\$) |
|----------------------|------------|--------------|
| POMONA 3925-0 0.090" | 668-198    | 124.00       |

#### Pomona 4176

##### 袖珍微型測試鉤套件

##### Minigrabber Test Clip Kit

- \* Kit contains 2 pcs. of 3925, one black/one red
- \* Insulation : Glass filled nylon
- \* Marking : Pomona 3925"
- \* Hand-held testing : 30VAC/60VDC Max.
- \* Body : Contact - Gold Plated Beryllium Copper, Spring - Stainless Steel



| MODEL          | STOCK CODE | PRICE (HK\$) |
|----------------|------------|--------------|
| POMONA 4176-02 | 668-201    | 25.00        |

#### Pomona 4555

##### 袖珍微型測試鉤供最大

##### 0.144 直徑電線

##### Minigrabber Test Clip For Max.

##### 0.144 Wire Dia

- \* Contact : Gold Plated Beryllium Copper
- \* Spring : Stainless Steel
- \* Body Insulation: Glass filled nylon
- \* Hands free testing in controlled voltage environments: 300 VRMS Max.
- \* For CE compliance: not intended for hand-held use at voltage above 33 VRms/70 VDC



| MODEL                | STOCK CODE | PRICE (HK\$) |
|----------------------|------------|--------------|
| POMONA 4555-0 0.144" | 668-199    | 124.00       |

### 微型測試鉤 Grabber Test Clips

#### Pomona 4826

##### 袖珍微型測試鉤連插針式插座

##### Minigrabber Test Clip With Pin Tip Jack

- \* This Minigrabber test clip has a pin jack built right into the plunger
- \* Excellent for attaching the Grabber test clip directly to the end of a pin tip patch cord or it can be used as an adapter for miniature test probes with 2.0 (.080) tips
- \* Contact: Beryllium Copper per QQ-C-533, Alloy 165
- \* Spring : Stainless steel, 302



| MODEL         | STOCK CODE | PRICE (HK\$) |
|---------------|------------|--------------|
| POMONA 4826-0 | 668-203    | 52.00        |

#### Pomona 5522

##### 袖珍微型測試鉤套件

##### Minigrabber Test Clip Kit

- \* Kit contains 10 pcs. of 3925, one of each color
- \* Insulation : Glass filled nylon
- \* Marking : "Pomona 3925"
- \* Hand-held testing: 30VAC/60VDC Max.
- \* Body : Contact - Gold Plated Beryllium Copper, Spring - Stainless Steel



| STOCK CODE | PRICE       |
|------------|-------------|
| 668-202    | HK\$ 112.00 |

#### Pomona 6312

##### 微型 SMD 測試鉤連 IC 長尖針

##### Micro SMD Grabber Test Clip,

##### 8-.5 mm IC Long Tip

- \* Use with PQFP packages with 0.3mm lead pitch or greater
- \* 13mm long tip allows measurement at IC leads that are not easily accessible
- \* Thin body style allows an unlimited number of clips to be stacked side by side
- \* Maximum frequency is 100 MHz



| STOCK CODE | PRICE       |
|------------|-------------|
| 668-206    | HK\$ 666.00 |

#### Pomona 6352

##### 微型 SMD 測試鉤連 IC 長尖針 (10件)

##### Micro SMD GrabberR Test Clip,

##### 8-.5 mm IC Long Tip (10 Pcs.)

- \* Use with PQFP packages with 0.3mm lead pitch or greater
- \* 13mm long tip allows measurement at IC leads that are not easily accessible
- \* Thin body style allows an unlimited number of clips to be stacked side by side
- \* Maximum frequency is 100 MHz



| STOCK CODE | PRICE         |
|------------|---------------|
| 668-207    | HK\$ 3,216.00 |

### PLCC測試鉤連配線

### PLCC Test Clips

#### Pomona 5279

##### 微型測試鉤連配線套件

##### SMD Grabber Test Clip Patch Cord Kit

- \* Gold plated upper contacts assure noise free, low resistance connections
- \* Standard .025 square pins accept wire-wrap, .025 sq. receptacle or soldered wires
- \* Pins are staggered to use the least space
- \* Gold plated lower contacts assure the best connection the chip leads
- \* Material : Gray, glass-filled nylon




| MODEL       |           | STOCK CODE | PRICE (HK\$) |
|-------------|-----------|------------|--------------|
| POMONA 5279 | 20 pin    | 668-064    | 180.00       |
| POMONA 5280 | 28 pin    | 668-065    | 295.00       |
| POMONA 5281 | 32 pin    | 668-066    | 311.00       |
| POMONA 5282 | 44 pin    | 668-067    | 347.00       |
| POMONA 5283 | 52 pin    | 668-068    | 409.00       |
| POMONA 5284 | 68 pin    | 668-069    | 462.00       |
| POMONA 5285 | 84 pin    | 668-070    | 551.00       |
| POMONA 5286 | 20-84 pin | 668-071    | 2,265.00     |

### QFP 鉗座 QFP Clips

#### Pomona 5643

##### 測試鉗, 100 管腳

- \* Test Clip, 100 pin, .65mm (3.9)
- \* Interfaces with high density QFP surface mount chips
- \* Gold plated connector pins and contacts assure noise free connections
- \* Two stage alignment assures positive connections
- \* Gold plated .025" square pins provide easy connection with either ribbon cable or discrete jumpers



| STOCK CODE | PRICE         |
|------------|---------------|
| 668-030    | HK\$ 2,088.00 |

#### Pomona 5643L

##### 測試鉗, 100 管腳連鎖

##### Test Clip, 100 pin, .65mm (3.9),

##### Locking

- \* Centrally activated locking mechanism allows testing vertical boards
- \* Interfaces with high density EIAJ QFP surface mount chip leads
- \* Two stage alignment assures positive connections
- \* Gold plated connector pins and contacts assure noise free connections



| STOCK CODE | PRICE         |
|------------|---------------|
| 668-031    | HK\$ 2,265.00 |

#### Pomona 5644

##### 測試鉗, 120 管腳

##### Test Clip, 120p QFP (3.9)

- \* Interfaces with high density EIAJ PQFP surface mount chip leads
- \* Two-stage alignment assures positive connections
- \* Gold plated connector pins and contacts assure noise free connections
- \* Gold plated .025" square pins provide easy connection with either ribbon cable or discrete jumpers



| STOCK CODE | PRICE         |
|------------|---------------|
| 668-037    | HK\$ 2,354.00 |

#### Pomona 5645

##### 測試鉗, 160 管腳

##### Test Clip, 160 pin (3.9)

- \* Interfaces with high density 160 Pin EIAJ QFP surface mount chip leads
- \* Two stage alignment assures positive connections
- \* Gold plated connector pins and contacts assure noise free connections



| STOCK CODE | PRICE         |
|------------|---------------|
| 668-042    | HK\$ 2,754.00 |

#### Pomona 5645L

##### 測試鉗, 160 管腳連鎖

##### Test Clip, 160 pin (3.9), Locking

- \* Two stage alignment assures positive connections
- \* Centrally activated locking mechanism allows testing vertical boards
- \* Interfaces with high density 160 Pin EIAJ QFP surface mount chip leads
- \* Gold plated connector pins and contacts assure noise free connections



| STOCK CODE | PRICE         |
|------------|---------------|
| 668-043    | HK\$ 3,020.00 |

#### Pomona 5888-2

##### 測試鉗, 64 管腳

##### Test Clip, 64 pin QFP, 0.8mm, (3.9)

- \* Interfaces with high density QFP surface mount chips
- \* Two-stage alignment assures positive connections
- \* Gold plated connector pins and contacts assure noise free connections



| STOCK CODE | PRICE         |
|------------|---------------|
| 668-024    | HK\$ 3,908.00 |


QFP 鉗座  
QFP Clips

Pomona®

## Pomona 5998A

240 管腳塑膠封裝 QFP 連 PGA 插座  
240 Pin Plastic QFP With PGA Socket

- \* A custom designed interface with high density plastic, metal and ceramic QFP surface mount chip leads
- \* Two-stage alignment assures positive connection
- \* Gold plated contacts and PGA sockets assure noise free connections
- \* PGA sockets fit standard PGA pins



STOCK CODE : 668-055

PRICE : HK\$ 6,884.00

## Pomona 6150

測試鉗, 100 管腳 TQFP 連鎖  
Test Clip, 100 Pin TQFP, Locking

- \* Connects to high-density plastic TQFP or SQFP surface mounted chip leads
- \* Locking feature insures positive retention on the chip in either vertical or horizontal position
- \* Gold plated contacts for the chip leads and the connector pins assure noise free connection



STOCK CODE : 668-034

PRICE : HK\$ 3,553.00

SOIC 及 SSOP 測試鉗  
SOIC & SSOP Clips

Pomona®

## Pomona 5250

SOIC 測試鉗  
SOIC Clip

- \* Upper contacts are .025" sq. pins, spaced at .100". Pins are perfect for sq. pin receptacles, wire-wrap or jumper leads
- \* Gold plated lower contacts assure reliable, noise free connections
- \* Molded barriers between each contact allow connections to be made on live boards without accidental shorting to adjacent chip leads



| MODEL       |             | STOCK CODE | PRICE (HK\$) |
|-------------|-------------|------------|--------------|
| POMONA 5250 | 8 pin       | 667-216    | 74.00        |
| POMONA 5251 | 14 pin      | 667-217    | 81.00        |
| POMONA 5252 | 16 pin      | 668-114    | 88.00        |
| POMONA 5253 | 20 pin      | 668-115    | 101.00       |
| POMONA 5254 | 24 pin      | 668-116    | 148.00       |
| POMONA 5437 | 28 pin      | 668-117    | 180.00       |
| POMONA 5514 | 6 clips kit | 667-218    | 590.00       |

## Pomona 5413

SOIC 測試鉗, 14 管腳  
SOIC Clip, 14 Pin

- \* Can be used with flying leads for multiple connections
- \* Molded barriers between each contact allows connections to be made without accidental shorting of adjacent contacts
- \* Square pins .025" (0.63) provide access points for individual pin testing or the use of individual .025" (0.63) square pin connectors



STOCK CODE : 668-113

PRICE : HK\$ 105.00

## Pomona 6107

SOIC 測試鉗  
SOIC Clip

- \* Gold plated upper contacts fit standard double row ribbon cable connectors
- \* Gold plated lower contacts assure reliable, noise free connections
- \* Molded barriers between each contact allow connections to be made on live boards without accidental shorting to adjacent chip leads
- \* Open back of clip allows probing of chip leads while the clip is attached



| MODEL       | STOCK CODE | PRICE (HK\$) |
|-------------|------------|--------------|
| POMONA 6107 | 668-118    | 258.00       |
| POMONA 6108 | 668-119    | 287.00       |

SOIC 及 SSOP 測試鉗  
SOIC & SSOP Clips

Pomona®

## Pomona 6109

SOIC 測試鉗, 44 管腳  
SOIC Clip, 44 pin

- \* Gold plated upper contacts fit standard double row ribbon cable connectors
- \* Gold plated lower contacts assure reliable, noise free connections
- \* Molded barriers between each contact allow connections to be made on live boards without accidental shorting to adjacent chip leads



STOCK CODE : 667-219

PRICE : HK\$ 311.00

香蕉型轉接頭及插座  
Banana Plugs and Jacks

Pomona®

## Pomona 1325

香蕉插頭 (非焊接式)  
Banana Plug, Solderless

- \* Designed to fit on the end of any 22 AWG to 18 AWG wire
- \* Cross hole wire entry fits wires up to .12" (3mm) diameter
- \* Set screw clamps wire firmly with flat blade screwdriver
- \* Available with tarnish resistant nickel or gold plating for very low contact resistance



| MODEL         | STOCK CODE | PRICE (HK\$) |
|---------------|------------|--------------|
| POMONA 1325-0 | 668-592    | 116.00       |
| POMONA 5406-0 | 668-593    | 23.00        |
| POMONA 5230-0 | 668-594    | 156.00       |

## Pomona 1330

雙香蕉型接頭, 非焊接式零件鑲嵌區  
Double Banana Plug, Solderless,  
With Component Mounting Area

- \* Features a recessed area for mounting small discrete components with set screws
- \* For test versatility, banana plugs can be vertically and horizontally stacked to the adapter
- \* The Banana Plug features Nickel Plated, Beryllium Copper for tarnish resistance & long insertion life



| MODEL         | STOCK CODE | PRICE (HK\$) |
|---------------|------------|--------------|
| POMONA 1330-0 | 668-620    | 22.00        |

## Pomona 1390

獨立式香蕉型插座  
Banana Plug, Isolation

- \* Provides two-terminal isolation
- \* Top stack-up receptacles isolated from lower plug to permit addition of series resistors, diodes...etc
- \* Ideal for computers, lab, circuit design and testing
- \* Bright tin plated solder turret terminals for permanent noise-free connections



| MODEL         | STOCK CODE | PRICE (HK\$) |
|---------------|------------|--------------|
| POMONA 1390-0 | 668-624    | 51.00        |

## Pomona 1581

測試鉗, 160 管腳 (3.9), 連鎖  
Test Clip, 160 pin (3.9), Locking

- \* Banana Jacks mount into panels ranging in thickness from .063" (1.6mm) to .375" (9.5mm)
- \* Model 1581 features bright tin plating
- \* Insulators : Polycarbonate



| MODEL         | STOCK CODE | PRICE (HK\$) |
|---------------|------------|--------------|
| POMONA 1581-0 | 668-607    | 84.00        |
| POMONA 2854-0 | 668-608    | 169.00       |
| POMONA 4900-0 | 668-609    | 124.00       |

## Pomona 1825

非焊接式拼體型香蕉插連安全軸環  
Solderless Stackup Banana Plug  
With Safety Collar

- \* Compatible with 18 to 22 AWG wire
- \* Easy solderless wire attachment by means of an internal set screw
- \* Integral safety collar insulates wire conductor and offers wire strain relief
- \* Banana Plug/Jack springs are beryllium copper for long insertion life



| MODEL         | STOCK CODE | PRICE (HK\$) |
|---------------|------------|--------------|
| POMONA 1825-0 | 668-597    | 116.00       |
| POMONA 4899-0 | 668-598    | 151.00       |

香蕉型轉接頭及插座  
Banana Plugs and Jacks

Pomona®

## Pomona 1837

雙香蕉型插塞帶3個獨立接頭  
Double Banana Plug, Three  
Terminal Isolation

- \* Operating Voltage : 2500 VDC
- \* Current : 15 Amperes
- \* Lower Connector : Double Banana Plug
- \* Used to make your own attenuator, balun or filter
- \* Contact Resistance : Less than .001Ω per banana plug



STOCK CODE : 668-623

PRICE : HK\$ 103.00

## Pomona 2142

被絕緣微型香蕉插座  
Insulated Miniature Banana Jack

- \* Accepts miniature banana plugs
- \* Mounts in panels up to .250" thick
- \* Rating : 1500 VDC, 5 Amps, +115 °C(+239 °F) Max



| MODEL         | STOCK CODE | PRICE (HK\$) |
|---------------|------------|--------------|
| POMONA 2142-0 | 668-564    | 107.00       |

## Pomona 2143

微型雙香蕉插座  
Double Miniature Banana Jack

- \* Accepts miniature banana plugs
- \* Mounts in panels up to .188" thick
- \* Rating : 1500 VRMS, 5 Amps, +115 °C(+239 °F) Max
- \* Color : One Red and one Black
- \* Banana Jack Insulation: Polycarbonate
- \* Panel Insulator : Polycarbonate



| MODEL         | STOCK CODE | PRICE (HK\$) |
|---------------|------------|--------------|
| POMONA 2143-0 | 668-525    | 29.00        |

## Pomona 2244

被絕緣微型香蕉夾  
Miniature Double Banana Plug

With Setscrews

- \* Internal setscrews to secure cable or component leads
- \* Accommodates 3.8 (.15) dia. cable
- \* Operating Voltage : 2500 VDC
- \* Current : 5 Amperes Cont.



| MODEL         | STOCK CODE | PRICE (HK\$) |
|---------------|------------|--------------|
| POMONA 2244-0 | 668-543    | 39.00        |

## Pomona 2269

雙香蕉插座, 控制板鑲嵌式底座  
Double Banana Jack, Panel Mount, Base

- \* Mounts in panels from 1.60 (.063) to 9.53 (.375) thick
- \* Banana Jack : Bright Tin Plated Brass
- \* Mounting Base : Polycarbonate
- \* Insulator : Polycarbonate



| MODEL         | STOCK CODE | PRICE (HK\$) |
|---------------|------------|--------------|
| POMONA 2269-0 | 668-611    | 23.00        |
| POMONA 5233-0 | 668-612    | 35.00        |

## Pomona 2970

三個一組香蕉夾, 非焊接式  
Triple Banana Plug, Solderless

- \* Set screws secure leads
- \* Ideal for balanced line 2 conductor shielded cable assemblies
- \* Operating Voltage : 5000 VDC
- \* Current : 15 Amperes Cont.
- \* Capacitance : 0.8 pf at 10 MHz



| MODEL         | STOCK CODE | PRICE (HK\$) |
|---------------|------------|--------------|
| POMONA 2970-0 | 668-626    | 40.00        |

香蕉型轉接頭及插座  
Banana Plugs and Jacks

Pomona®

## Pomona 3030

- 短棒雙香蕉插座  
Double Miniature Banana Plug  
Shorting Bar
- \* Low profile 1.6 (.062) thick brass shorting bar
  - \* Center hole accepts #4-40 screw, for easy removal
  - \* Mates to Model # 2143 or any miniature double banana jack
  - \* Current : 5 Amperes
  - \* Resistance : Resistance less than 1.5 milliohms



STOCK CODE : 668-552      PRICE : HK\$ 30.00

## Pomona 3257

- 香蕉插座, 鋼釘 0.062 嵌板  
Banana Plug, Rivet For .062 Panel
- \* Excellent for riveting to panels or boards
  - \* Fits standard (.166 dia.) banana jack
  - \* Operating Voltage : 5000 VDC
  - \* Current : 15 Amperes
  - \* Banana Plug Body : Brass, Alloy 360, Annealed



| MODEL       | STOCK CODE | PRICE (HK\$) |
|-------------|------------|--------------|
| POMONA 3257 | 668-627    | 116.00       |
| POMONA 3258 | 668-628    | 116.00       |

## Pomona 3263

- 香蕉插座 6-32 X1/2 螺栓釘  
Banana Plug With 6-32 X 1/2 Stud
- \* Working Voltage : 5000 VRMS
  - \* Threaded stud for rapid mounting
  - \* Furnished with hex nut and tin plated solder lug
  - \* Ideal for connecting power supplies or test equipment to prototype circuit boards
  - \* Mates to Model #1581 or any standard banana jack



| MODEL       | STOCK CODE | PRICE (HK\$) |
|-------------|------------|--------------|
| POMONA 3263 | 668-586    | 133.00       |
| POMONA 3264 | 668-587    | 133.00       |
| POMONA 4511 | 668-588    | 160.00       |
| POMONA 4512 | 668-589    | 160.00       |

## Pomona 3265

- 香蕉插座 6-32 X1/4 螺釘  
Banana Plug With 6-32 X 1/4 Screw
- \* Fits standard (.166 dia.) banana jack
  - \* Operating Voltage : 5000 VRMS MAX
  - \* Current : 15 Amperes
  - \* Banana Plug Body : Brass, Alloy 360, 1/2 Hard
  - \* Spring : Beryllium Copper, Berylico 25, Cond. H.T.



| MODEL       | STOCK CODE | PRICE (HK\$) |
|-------------|------------|--------------|
| POMONA 3265 | 668-590    | 160.00       |
| POMONA 3266 | 668-591    | 160.00       |

## Pomona 3267

- 香蕉插座 1/4-32 螺紋及鑽孔型  
Banana Jack With 1/4-32 Thread & Through-Hole
- \* Fits standard banana plug
  - \* 1/4 - 32 Thread
  - \* Banana Jack Body : Nickel Plated Brass
  - \* Solder Lug : Copper, finish - Hot tin dip



STOCK CODE : 668-573      PRICE : HK\$ 80.00

## Pomona 3268

- 微型香蕉夾, 鋼釘.062" ~0.125"  
嵌板  
Miniature Banana Plug, Rivet For .062" ~ 0.125" Panel
- \* Excellent for riveting to panels or boards
  - \* Banana features gold plated Beryllium Copper for long insertion life and corrosion resistance
  - \* Operating voltage : 2500 VDC
  - \* Current : 5A max.



| MODEL       | STOCK CODE | PRICE (HK\$) |
|-------------|------------|--------------|
| POMONA 3268 | 668-553    | 93.00        |
| POMONA 3271 | 668-554    | 93.00        |
| POMONA 3272 | 668-555    | 93.00        |
| POMONA 3273 | 668-556    | 93.00        |

香蕉型轉接頭及插座  
Banana Plugs and Jacks

Pomona®

## Pomona 3276

- 微型香蕉插塞, 螺栓連接臺  
Miniature Banana Plug, 4-40x.230"  
Stud With Solder Turret
- \* Threaded stud enables fast and easy mounting to panels
  - \* Solder turret allows wire attachment
  - \* Miniature banana plug spring features gold plated Beryllium Copper for long insertion life and low contact resistance



| MODEL       | STOCK CODE | PRICE (HK\$) |
|-------------|------------|--------------|
| POMONA 3276 | 668-547    | 107.00       |
| POMONA 4513 | 668-548    | 156.00       |

## Pomona 3277

- 微型香蕉插座, 鋼釘.062" 嵌板  
Miniature Banana Jack, Rivet For .062 Panel
- \* Accepts miniature banana plugs
  - \* Mounts in panels up to .062" thick
  - \* Operating Voltage : 1500 VDC
  - \* Current : 5 Amperes
  - \* Miniature Banana Jack : Brass



| MODEL         | STOCK CODE | PRICE (HK\$) |
|---------------|------------|--------------|
| POMONA 3277-0 | 668-530    | 71.00        |

## Pomona 3690

- 焊接類微型香蕉夾  
Solder Type Miniature Banana Plug
- \* Supports 20 to 22 AWG wires
  - \* Allows creation of custom patch cord lengths
  - \* Insulator unthreads to allow easy Do-It-Yourself wire soldering
  - \* Banana plug body & spring are gold plated for corrosion resistance and optimum electrical connection between plug and jack
  - \* Banana plug spring is Beryllium Copper for superior spring shape retention to ensure long insertion life



| MODEL         | STOCK CODE | PRICE (HK\$) |
|---------------|------------|--------------|
| POMONA 3690-0 | 668-545    | 156.00       |
| POMONA 4617-0 | 668-548    | 27.00        |

## Pomona 4005

- 香蕉插座.025" 方形針  
Banana Jack With .025" Square Pin
- \* Mounts in panels from 1.60 (.063) to 9.53 (.375) thick
  - \* Banana Jack : Nickel Plated Brass
  - \* Terminal : Gold Plated Phosphor Bronze
  - \* Insulation : Polycarbonate
  - \* Hand-held testing : 30VAC/60VDC Max.



| MODEL         | STOCK CODE | PRICE (HK\$) |
|---------------|------------|--------------|
| POMONA 4005-0 | 668-567    | 187.00       |

## Pomona 4022

- 微型香蕉插座連繞線終端  
Miniature Banana Jack With Wire Wrap Terminal
- \* Accepts miniature banana plugs
  - \* Mounts in panels up to .250" thick
  - \* Operating Voltage : 1500 VDC
  - \* Current : 3 Amperes



| MODEL         | STOCK CODE | PRICE (HK\$) |
|---------------|------------|--------------|
| POMONA 4022-0 | 668-529    | 160.00       |

## Pomona 4163

- 三個一組香蕉插座  
Triple Banana Jack For Seimens Plug
- \* Mounts in panels at 17.78 (.70) thickness
  - \* Accepts standard banana plugs up to .80 long
  - \* Initial connection made with ground receptacle
  - \* Banana Jack : Bright Tin Plated Brass
  - \* Hand-held testing : 30VAC/60VDC Max.



| MODEL         | STOCK CODE | PRICE (HK\$) |
|---------------|------------|--------------|
| POMONA 4163-0 | 668-574    | 51.00        |

香蕉型轉接頭及插座  
Banana Plugs and Jacks

Pomona®

## Pomona 4590

- 基底托架, 三個或二個一組,  
微型香蕉插座  
Mounting Base, Triple Double  
Miniature Banana Jack
- \* Body : Polycarbonate
  - \* Color : Black and Red
  - \* Operating Temperature: +115 °C (+239 °F) Max.



| MODEL                  | STOCK CODE | PRICE (HK\$) |
|------------------------|------------|--------------|
| POMONA 4590-0 (Triple) | 668-572    | 80.00        |
| POMONA 4614-0 (Triple) | 668-570    | 71.00        |
| POMONA 4619-0 (Double) | 668-569    | 44.00        |
| POMONA 4654-0 (Double) | 668-571    | 44.00        |

## Pomona 4601

- 三個一組香蕉插座, .75" 間隔, 黑色  
Triple Banana Jack, .75" Spacing, Black
- \* Closed entry receptacle, 4.2 (.166) dia. x 23.4 (.920) deep
  - \* Mounts in panels from 1.6 (.063) to 9.5 (.375) thick
  - \* Nickel plated lock washer and 1/4 ~ 32 hex nut
  - \* Ideal for connection to power supplies with positive, negative and return connections



| MODEL         | STOCK CODE | PRICE (HK\$) |
|---------------|------------|--------------|
| POMONA 4601-0 | 668-613    | 37.00        |

## Pomona 4653

- 三個一組, 微型香蕉夾, 非焊接式  
Triple, Miniature Banana Plug, Solderless
- \* Use for balanced line 2 conductor shielded cable assemblies
  - \* Operating Voltage : 2500 VDC
  - \* Current : 5 Amperes
  - \* Operating Temperature: +50 °C (+122 °F) Max.



| MODEL         | STOCK CODE | PRICE (HK\$) |
|---------------|------------|--------------|
| POMONA 4653-0 | 668-544    | 101.00       |

## Pomona 4892

- 二個一組, 微型香蕉夾,  
非焊接式, 鍍金的  
Double Banana Plug, Solderless, Gold-Plated
- \* Simplified attachment of cables or small components by means of set screws
  - \* For test versatility, banana plugs can be vertically stacked
  - \* Banana plug spring is Beryllium Copper for long insertion life



| MODEL         | STOCK CODE | PRICE (HK\$) |
|---------------|------------|--------------|
| POMONA 4892-0 | 668-616    | 39.00        |
| POMONA 4898-0 | 668-617    | 22.00        |

## Pomona 4933

- 香蕉型插護套供 AWG 金屬線  
Sheathed Banana Plug For AWG Wire
- \* Pomona 4933 for 18,20,22 AWG Wire
  - \* Pomona 4986 for 14, 16 AWG Wire
  - \* Threaded two piece design allows wires to be soldered or crimped to the banana plug
  - \* Heavy-duty plastic body withstands cracking if accidentally dropped
  - \* Banana plug spring is nickel plated Beryllium Copper for long insertion life



| MODEL         | STOCK CODE | PRICE (HK\$) |
|---------------|------------|--------------|
| POMONA 4933-0 | 668-515    | 28.00        |
| POMONA 4986-0 | 668-516    | 28.00        |

## Pomona 4934

- 香蕉型插護套供 AWG 金屬線  
Sheathed Banana Plug For AWG Wire
- \* Heavy-duty plastic body withstands cracking if accidentally dropped
  - \* Fits into Pomona Models 4933 & 4986 Banana Plugs
  - \* Threaded two piece design allows wires to be soldered or crimped to the banana jack body
  - \* Current : 15 Amps Max.



| MODEL                                   | STOCK CODE | PRICE (HK\$) |
|-----------------------------------------|------------|--------------|
| POMONA 4934-0 (for AWG wire 18, 20, 22) | 668-517    | 29.00        |
| POMONA 4987-0 (for AWG wire 14, 16)     | 668-518    | 29.00        |

香蕉型轉接頭及插座  
Banana Plugs and Jacks

Pomona®

## Pomona 5145

- 雙香蕉夾，短棒，被絕緣的  
Double Banana Plug Shorting Bar, Insulated
- \* Low profile, completely insulated shorting bar
  - \* Insulation has finger ridge for ease of insertion and removal
  - \* Mates to Model #2269 or any standard double banana jack
  - \* Current : 15 Amperes
  - \* Resistance : Less than 1.5 milliohms installed



STOCK CODE : 668-111

PRICE : HK\$ 47.00

## Pomona 5165

- 雙香蕉夾，短棒，接線柱  
Double Banana Plug Shorting Bar With Binding Post
- \* Mates to Model #2269 or any standard double banana jack
  - \* Binding post cross hole allows attachment of pin tip plugs
  - \* Shorting bar is completely encapsulated in clear polypropylene
  - \* Operating Voltage : 2500 VRMS

MODEL  
POMONA 5165-0STOCK CODE  
668-541PRICE ( HK\$ )  
78.00

## Pomona 5167

- 香蕉插座供 18-20 AWG 金屬線  
Banana Jack For 18 - 20 AWG Wire
- \* This in-line banana jack is ideal for making patch cords and field repairs
  - \* A snap-on two piece design allows the wire to be crimped or soldered to the banana jack
  - \* Part will accept 18, 20, 22 AWG wire, crimp or solder connection
  - \* POMONA 5168-0 is 14 AWG

MODEL  
POMONA 5167-0STOCK CODE  
668-565PRICE ( HK\$ )  
187.00

POMONA 5168-0

STOCK CODE  
668-566PRICE ( HK\$ )  
19.00

## Pomona 5169

- 香蕉插座供 18-20 AWG 金屬線  
Banana Plug For 18 - 20 AWG Wire
- \* This in-line banana plug is ideal for making patch cords and field repairs
  - \* A snap-on two piece design allows the wire to be crimped or soldered to the banana plug
  - \* Parts will accept 18, 20, 22 AWG. Wire, crimp or solder connection

MODEL  
POMONA 5169-0STOCK CODE  
668-599PRICE ( HK\$ )  
19.00

## Pomona 5170

- 香蕉插座供 14-16 AWG 金屬線  
Banana Plug For 14 - 16 AWG Wire
- \* Insulation : Flexible PVC
  - \* Ideal for making test cables and field repairs
  - \* Use with Model #5168 Banana Jack to make extension cables
  - \* Part will accept 14, 16 AWG wire, crimp or solder connection
  - \* Snap-on two piece design allows the wire to be crimped or soldered

MODEL  
POMONA 5170-0STOCK CODE  
668-600PRICE ( HK\$ )  
19.00

## Pomona 5931

- 4mm 香蕉型插護套  
Sheathed 4mm Banana Jack
- \* Banana jack mates to Pomona's models 5907A, 5908A & 5909A flexible sheathed style of DMM test leads
  - \* Slip ring threads onto the insulated body to firmly secure jack to panel
  - \* Banana jack is gold plated for superb electrical connection
  - \* Operating Voltage : 1000 VRMS Max.

MODEL  
POMONA 5931-0STOCK CODE  
668-604PRICE ( HK\$ )  
173.00香蕉型轉接頭及插座  
Banana Plugs and Jacks

Pomona®

## Pomona 5932

- 4mm 接線柱  
4mm Binding Post
- \* Five way binding post attachment
  - \* Including Wire, Banana plug, Pin tip plug, DMM probe tip and Spade lug attachment
  - \* Binding post is metric in design
  - \* Solder turret at bottom enables permanent wire attachment
  - \* Operating : 750VRMS , 25A MAX



(10 pcs / Pack)

MODEL  
Pomona 5932-0  
Pomona 5932-2  
Pomona 5932-6Color  
Black  
Red  
BlueSTOCK CODE  
668-605  
668-667  
668-666PRICE ( HK\$ )  
17.90  
17.90  
17.90

## Pomona 5933

- 香蕉插座，4mm，同軸  
Banana Jack, 4mm, In-Line
- \* Ideal for panel mount applications
  - \* .079" (2mm) opening at bottom of jack enables solder type wire attachment
  - \* Insulator & Collars : Nylon, Color Per Part Number
  - \* Banana Jack & Nut : Brass, Nickel Plated

MODEL  
POMONA 5933-0STOCK CODE  
668-606PRICE ( HK\$ )  
67.00

## Pomona 5934

- 香蕉插塞，4mm，同軸  
Banana Plug, 4mm, In-Line
- \* Easy to assemble threaded two piece construction enables solderless wire attachment by means of an internal set screw
  - \* Compatible with 18 to 22 AWG wire
  - \* Banana plug spring is Beryllium Copper for long insertion life
  - \* Banana plug body and spring are nickel plated for tarnish resistance

MODEL  
POMONA 5934-0STOCK CODE  
668-601PRICE ( HK\$ )  
89.00

## Pomona 5935

- 2mm 絕緣式香蕉插座  
2mm Insulated Banana Jack
- \* Banana jack is insulated from the panel
  - \* Solder hole at the bottom of the jack allows for 18 to 22 AWG wire attachment
  - \* Offered in six popular colors
  - \* Recommended maximum panel thickness : .31" (8,0 mm)

MODEL  
POMONA 5935-0STOCK CODE  
668-602PRICE ( HK\$ )  
46.00

## Pomona 5936

- 香蕉插塞，2mm  
Banana Plug, 2mm
- \* Beryllium Copper spring offers long insertion life
  - \* Compatible with 18 to 22 AWG wire
  - \* Available in six colors
  - \* Banana Plug : Body - Brass, Nickel Plated
  - \* Threaded two piece design allows wires to be soldered to the banana plug

MODEL  
POMONA 5936-0  
POMONA 4898-0STOCK CODE  
668-603  
668-617PRICE ( HK\$ )  
39.00  
22.00

## Pomona MDP-ST

- 雙香蕉插塞連桿接臺  
Double Banana Plug With Solder Turrets
- \* Simplified attachment of cables or small components by means of solder turrets
  - \* For test versatility, banana plugs can be vertically stacked to the banana plug
  - \* Banana plug spring is Beryllium Copper for long insertion life



STOCK CODE : 668-618

PRICE : HK\$ 28.00

香蕉型轉接頭及插座  
Banana Plugs and Jacks

Pomona®

## Pomona MDP-X

- 雙香蕉插塞連絕緣焊接頭  
Double Banana Plug With Isolation Solder Terminals
- \* Mates to Model #2269 or any standard double banana jack
  - \* Provides four terminal isolation
  - \* Top stack-up receptacles isolated from lower plugs
  - \* Ideal for insertion of matching network in laboratory VTM's signal generators...etc
  - \* Bright tin plated solder turret terminals for permanent noise-free connections



STOCK CODE : 668-622

PRICE : HK\$ 91.00

## Pomona 2382

- 微型接線柱  
Miniature Binding Post
- \* Accepts miniature banana plug
  - \* #8-32 hex nut and lockwasher included
  - \* Operating Voltage : 1500 VRMS
  - \* Pomona 2382 : Gold-plated
  - \* Pomona 2439 : Tin-plated

MODEL  
POMONA 2382-0  
POMONA 2439-0STOCK CODE  
668-557  
668-558PRICE ( HK\$ )  
37.00  
28.00

## Pomona 2383

- 微型絕緣接線柱連雙托架基底  
Miniature Insulating Binding Post With Double Mounting Base
- \* Accepts miniature banana plugs
  - \* #8-32 hex nut and lockwasher included
  - \* Mounts in panels up to 4.8 (.188) thick
  - \* Finish (Pomona 2383) : Gold plated brass
  - \* Finish (Pomona 2440) : Model 2440 Tin plated brass

MODEL  
POMONA 2383-0  
POMONA 2440-0STOCK CODE  
668-559  
668-560PRICE ( HK\$ )  
71.00  
58.00

## Pomona 3750

- 接線柱  
Binding Post
- \* Mounts in panels from 1.57 (.062) to 6.35 (.250) thick
  - \* Crosshole is perpendicular with flat on mounting base
  - \* Insulated Captive Thumb Nut: Brass
  - \* Pomona 3750 : Binding Post, Gold PLT (Black)
  - \* Pomona 3760 : Binding Post, Tin PLT.(Black)
  - \* Pomona 3770 : Binding Post, Gold Plated Tellurium (Black)

MODEL  
POMONA 3750-0  
POMONA 3760-0  
POMONA 3770-0STOCK CODE  
668-575  
668-576  
668-577PRICE ( HK\$ )  
33.00  
23.00  
46.00

## Pomona 3862

- 雙托架基底，兩個 / 三個一組接線柱  
Mounting Base, Double/Triple Binding Post
- \* Pomona 3862 : Double binding post
  - \* Pomona 3863 : Triple binding post
  - \* Body : Polycarbonate
  - \* Color : Black and Red
  - \* Marking : Pomona Electronics Calif.

MODEL  
POMONA 3862-0  
POMONA 3863-0STOCK CODE  
668-584  
668-585PRICE ( HK\$ )  
53.00  
71.00

## Pomona 4098

- 接線柱，.025" 方形管腳  
Binding Post With .025" Square Pin
- \* Accepts standard banana plugs
  - \* Mounts in panels from 1.57 (.062) to 6.35 (.250) thick
  - \* Hand-held testing : 30VAC/60VDC Max.
  - \* Finish : Nickel plated brass
  - \* Current : 3 Amperes

MODEL  
POMONA 4098-0STOCK CODE  
668-581PRICE ( HK\$ )  
43.00

## 香蕉型轉接頭及插座

## Banana Plugs and Jacks

Pomona®

## Pomona 4115

## 短路鏈環供接線柱

## Shorting Link For Binding Posts

- \* Brass per QQ-B-613, Composition #2, 1/2 hard
- \* Finish : Nickel plate per QQ-N-290, latest revision, class 2, sulfate process .0002/.0003, full bright



STOCK CODE : 668-580

PRICE : HK\$ 80.00

## Pomona 4243

## 雙接線柱

## Double Binding Post

- \* Accepts standard banana plugs
- \* Mounts in panels from 1.57 (.062) to 6.35 (.250) thick
- \* Finish : Tin plated brass
- \* Insulation : Polycarbonate
- \* Hand-held testing : 30VAC/60VDC Max.



MODEL POMONA 4243-0

STOCK CODE 668-582

PRICE ( HK\$ ) 44.00

## Pomona 4995

## 接線柱

## Binding Post, Mil-P-55149/8

- \* Mounts in panels from 1.57 (.062) to 3.18 (.125) thick
- \* Complies to MIL-P-55149/8
- \* Body : Nickel plated brass
- \* Finish : Gold plated brass
- \* Hand-held testing : 30VAC/60VDC Max.



MODEL POMONA 4995-0

STOCK CODE 668-579

PRICE ( HK\$ ) 151.00

## Pomona 1286

## 雙香蕉插塞連接線柱

## Double Banana Plug With Binding Posts

- \* Converts Double Banana Jack Test Instruments to Binding Posts for test versatility
- \* Banana Plugs can be stacked vertically or horizontally
- \* Wires, spade lugs and pin tip plugs can be attached by means of the insulated knurl thumb knob
- \* Insulated knurl thumb knob is captive to prevent misplacement



MODEL POMONA 1286

STOCK CODE 668-538

PRICE ( HK\$ ) 70.00

POMONA 5405

STOCK CODE 668-539

PRICE ( HK\$ ) 102.00

## Pomona 1432

## 香蕉插座轉針型插塞

## Banana Jack To Pin Tip Plug

- \* Operating Voltage : 3000 VDC
- \* Current : 5 Amperes
- \* Lower Conn. : Pin Tip Plug
- \* Insulation : ABS molded to banana jack and pin tip body
- \* Permits banana plug cords to be used with equipment having pin tip jacks



MODEL POMONA 1432-0

STOCK CODE 668-536

PRICE ( HK\$ ) 98.00

## Pomona 1823

## 雙組香蕉插塞接合器

## Double Banana Plug Splice

- \* Provides rapid method for splicing cables
- \* Reduces necessity of storing extra long cables
- \* 4.2 (.166) dia. Banana Jacks
- \* Insulation : Polypropylene molded to Banana Jack bodies
- \* Operating Voltage : 5000 VDC



MODEL POMONA 1823-0

STOCK CODE 668-531

PRICE ( HK\$ ) 25.00

## 香蕉型轉接頭及插座

## Banana Plugs and Jacks

Pomona®

## Pomona 1829

## 單組香蕉插塞接合器

## Single Banana Plug Splice

- \* Provides a fast and easy method to splice two cables together to increase cable length
- \* Jacks : Brass, Nickel Plated
- \* Insulation : Polypropylene
- \* Operating Voltage : 5000 VDC
- \* Current : 15 Amperes Max.



MODEL POMONA 1829-0

STOCK CODE 668-537

PRICE ( HK\$ ) 129.00

## Pomona 2035

## 雙組微型香蕉插塞連短路棒

## Double Miniature Banana Plug, With Shorting Bar

- \* Provides a quick and easy means of shorting two inputs of a miniature double banana jack
- \* The plug to plug and jack to jack dimension is .500" (12.70mm) which is typical for double miniature banana plugs/jacks
- \* ABS body provides insulation protection to the user



MODEL POMONA 2035-0

STOCK CODE 668-551

PRICE ( HK\$ ) 42.00

## Pomona 2138

## 標準型香蕉插座轉微型香蕉插塞

## Standard Banana Jack To Miniature Banana Plug

- \* Permits standard banana plug to be used with equipment having miniature banana jacks
- \* Operating Voltage : 2500 VDC
- \* Current : 5 Amperes Cont.



MODEL POMONA 2138-0

STOCK CODE 668-533

PRICE ( HK\$ ) 178.00

## Pomona 2894

## 接線柱轉香蕉插塞

## Binding Post To Banana Plug

- \* Features insulated binding post for rapid mounting and interchangeability of components
- \* Center cross hole 4.2 (.166) dia.
- \* Provides side stackup connection
- \* Insulation : Polycarbonate. Color
- \* Operating Voltage : 2500 VDC



MODEL POMONA 2894-0

STOCK CODE 668-540

PRICE ( HK\$ ) 38.00

## Pomona 2952

## 雙組香蕉插座至微型香蕉插塞

## Double Banana Jack To Mini Banana Plug

- \* Operating Voltage : 2500 VDC.
- \* Current : 5 Amperes
- \* Permits Standard Double Banana Plug on 19.1 (.750) centers to be used with equipment having Miniature Double Jacks on 12.7 (.500) centers



STOCK CODE : 668-532

PRICE : HK\$ 65.00

## Pomona 3560

## 香蕉插塞測試接合器連 0.04 插座

## Banana Plug Test Adapter With .040 Socket

- \* An ideal test adapter for testing multi pin connectors
- \* Flexible tip allows easy access to adjacent pins
- \* Finish : Bright Tin plated
- \* Insulation : Polyvinyl chloride (PVC)
- \* Operating Voltage : 2500 VRMS



MODEL POMONA 3560-0

STOCK CODE 668-509

PRICE ( HK\$ ) 31.00

POMONA 3561-0

STOCK CODE 668-510

PRICE ( HK\$ ) 31.00

POMONA 3563-0

STOCK CODE 668-512

PRICE ( HK\$ ) 31.00

POMONA 3565-0

STOCK CODE 668-514

PRICE ( HK\$ ) 31.00

## 香蕉型轉接頭及插座

## Banana Plugs and Jacks

Pomona®

## Pomona 3562

## 香蕉插塞測試接合器

## 連 0.063 插座

## Banana Plug Test Adapter With .063 Socket

- \* An ideal test adapter for testing multi pin connectors
- \* Flexible tip allows easy access to adjacent pins
- \* Finish : Bright Tin plated
- \* Insulation : Polyvinyl chloride (PVC)
- \* Operating Voltage : 2500 VRMS
- \* Current : 13 Amperes



MODEL POMONA 3562-0

STOCK CODE 668-511

PRICE ( HK\$ ) 31.00

POMONA 3564-0

STOCK CODE 668-513

PRICE ( HK\$ ) 49.00

## Pomona 3744A

## 香蕉插座

## Banana Jack

- \* Operating Voltage : 5000 VDC
- \* Current : 15 Amperes
- \* Lower Conn. : Spade Lug
- \* Pomona 3744A : Banana Jack/Spade Lug #4-6 (Black)
- \* Pomona 3777A : Banana Jack/Spade Lug #8-10 (Black)



MODEL POMONA 3744A-0

STOCK CODE 668-112

PRICE ( HK\$ ) 12.00

POMONA 3777A-0

STOCK CODE 668-524

PRICE ( HK\$ ) 12.00

## Pomona 3834

## 針柱插塞至香蕉插塞聯結器

## Pin Tip Plug To Banana Plug Coupler

- \* Operating Voltage : 3000 VDC
- \* Current : 5 Amperes
- \* This splice accepts a standard banana plug on one end and a 2.0 (.080) pin tip plug on the other end
- \* Insulation : Polypropylene molded to banana jack body and pin tip body



MODEL POMONA 3834-0

STOCK CODE 668-542

PRICE ( HK\$ ) 27.00

## Pomona 4690

## 香蕉插塞測試接合器連 #22 插座

## Banana Plug Test Adapter With #22 Socket

- \* An ideal test adapter for testing multi pin connectors
- \* Flexible tip allows easy access to adjacent pins
- \* Finish : Bright Tin plated
- \* Insulation : Polyvinyl chloride (PVC)
- \* Operating Voltage : 2500 VRMS
- \* Current : 5 Amperes



MODEL POMONA 4690-0

STOCK CODE 668-507

PRICE ( HK\$ ) 31.00

POMONA 4691-0

STOCK CODE 668-508

PRICE ( HK\$ ) 31.00

## Pomona 5699

## 香蕉插座連終端螺絲釘

## Terminal Strip Banana Jack

- \* This adapter provides a banana jack connection by replacing the screw in a terminal strip
- \* Secure connections can be made with standard banana plug patch cords without breaking the connection to the terminal strip
- \* Banana jack .166 dia



MODEL POMONA 5699-0

STOCK CODE 668-521

PRICE ( HK\$ ) 29.00

POMONA 5700-0

STOCK CODE 668-522

PRICE ( HK\$ ) 29.00

POMONA 5701-0

STOCK CODE 668-523

PRICE ( HK\$ ) 29.00

## Pomona 6203

## 絕緣銲接頭配合萬用錶測試導線

## Insulated Spade Lug Set. Fits DMM Test Leads

- \* One Set = One Black + One Red



STOCK CODE : 668-519

PRICE : HK\$ 18.00



## 觸針插頭及插座 Pin Jacks and Plugs

### Pomona 1809

#### 觸針插座至香蕉插塞

#### Pin Jack To Banana Plug

- \* Operating Voltage : 2500 WVDC
- \* Current : 5 Amperes
- \* Permits pin tip cords to be used with equipment having banana jacks
- \* Insulation : ABS molded to pin jack and banana plug body



| MODEL         | STOCK CODE | PRICE (HK\$) |
|---------------|------------|--------------|
| POMONA 1809-0 | 668-535    | 178.00       |

### Pomona 3452

#### 短觸針插塞, 短路式

#### Pin Tip Plug, Shorted

- \* Operating Voltage : 3000 VRMS
- \* Current : 5 Amperes
- \* Ideal for providing a jumper on pin jack test boxes or panels
- \* Mates with Model #4543 or any other standard .080" pin jack
- \* Insulation : ABS molded to Pin Jacks and bodies



| MODEL         | STOCK CODE | PRICE (HK\$) |
|---------------|------------|--------------|
| POMONA 3452-0 | 668-562    | 39.00        |

### Pomona 3542

#### 觸針插座, 鍍金

#### Pin Tip Jack, Gold-Plated

- \* Operating Voltage : 1500 VDC
- \* Current : 5 Amperes
- \* Accepts .080 pin tip plugs
- \* Mounts in panels up to .250" thick
- \* Insulation : Polycarbonate - Molded to pin tip jack body



| MODEL         | STOCK CODE | PRICE (HK\$) |
|---------------|------------|--------------|
| POMONA 3542-0 | 668-527    | 124.00       |

### Pomona 4543

#### 雙重觸針插座

#### Double Pin Tip Jack

- \* Accepts .080 dia. pin
- \* Max. panel thickness .188
- \* Operating Voltage : 1500 VDC
- \* Current : 5 Amperes
- \* Pin Tip Jack Body : Gold Plated Brass H.H., Alloy 360
- \* Mounting Plate Insulation : Polycarbonate Thermoplastic



| MODEL         | STOCK CODE | PRICE (HK\$) |
|---------------|------------|--------------|
| POMONA 4543-0 | 668-526    | 33.00        |

### Pomona 4773

#### 觸針插座, 鍍金

#### Pin Tip Jack, Gold-Plated

- \* Accepts .080 dia. pin
- \* Max. panel thickness .25
- \* Operating Voltage : 1500 VDC
- \* Current : 3 Amperes
- \* Pin Jack Insulation : Polycarbonate molded to Pin Jack Body



| MODEL         | STOCK CODE | PRICE (HK\$) |
|---------------|------------|--------------|
| POMONA 4773-0 | 668-528    | 21.00        |

### Pomona 5173

#### 觸針插塞配 20AWG 金屬線

#### Pin Tip Plug For 20 AWG Wire

- \* Supports 18 20 & 22 AWG wires.
- \* This in-line 2.0 (.080) dia. pin tip plug is ideal for making patch cords and field repairs
- \* Parts will accept 18, 20, 22 AWG wire, crimp or solder connection
- \* A snap-on two piece design allows the wire to be crimped or soldered to the pin tip plug



| MODEL         | STOCK CODE | PRICE (HK\$) |
|---------------|------------|--------------|
| POMONA 5173-0 | 668-563    | 21.00        |

## 同軸電纜 BNC

### POMONA 2249-C-36

#### 電纜配線連 BNC 陽極接頭

#### Cable Assembly With BNC Male

- \* RG58C/U cable for test & measurement
- \* BNC male connector on each end
- \* Impedance : 50 ohm
- \* Length: 36"
- \* Gold plated center contacts assure the most noise free connection



| STOCK CODE : 668-234 | PRICE : HK\$ 99.00 |
|----------------------|--------------------|
|----------------------|--------------------|

## 示波器測試棒 Probe

### TEXAS Probe Series

#### 示波器測試棒

#### Oscilloscope Probe

- \* Probe frequency response that essentially can be considered transparent
- \* Meet IEC1010-2-031, 600Vpp, CATII
- \* Attenuator: X1 / X10
- \* System Bandwidth (3dB): 15/40 MHz
- \* System Rise-time: 23.3 / 8.75ns



| MODEL       | MHZ | STOCK CODE | PRICE (HK\$) |
|-------------|-----|------------|--------------|
| TEXAS 40/I  | 40  | 646-295    | 60.00        |
| TEXAS 60/I  | 60  | 646-296    | 75.00        |
| TEXAS 100/I | 100 | 646-297    | 115.00       |

## PRODUCT INTRODUCTION



[www.mobicon.com](http://www.mobicon.com)




## 老化測試座 Test and Burn-In Sockets

### IC51 Series

#### SOP 系列

#### SOP Series

- \* Sockets for SOP
- \* Custom design also available for multi-lead, fine-pitch and other special packages
- \* Material & Finish :  
Housing : PES (glass-filled), PEI (glass-filled), etc.  
Contacts : Copper alloy, gold plating over nickel



| MODEL           | 8 Pins  | STOCK CODE | PRICE (HK\$) |
|-----------------|---------|------------|--------------|
| IC51-0082-1024  | 8 Pins  | 667-079    | 272.00       |
| IC51-0162-1025  | 16 Pins | 667-062    | 285.00       |
| IC51-0162-1035  | 16 Pins | 667-123    | 235.00       |
| IC51-0162-1042  | 16 Pins | 667-054    | 280.00       |
| IC51-0222-793   | 22 Pins | 667-006    | 255.00       |
| IC51-0242-980   | 24 Pins | 667-007    | 254.00       |
| IC51-0262-645   | 26 Pins | 667-114    | 380.00       |
| IC51-0282-334-1 | 28 Pins | 667-112    | 300.00       |
| IC51-0302-1017  | 30 Pins | 667-092    | 250.00       |
| IC51-0302-914   | 30 Pins | 667-106    | 325.00       |
| IC51-0322-304-2 | 32 Pins | 667-070    | 305.00       |
| IC51-0322-667-2 | 32 Pins | 667-070    | 350.00       |
| IC51-0322-937   | 32 Pins | 667-044    | 280.00       |
| IC51-0402-708   | 40 Pins | 667-118    | 280.00       |
| IC51-0422-393   | 40 Pins | 667-069    | 325.00       |
| IC51-0442-1315  | 44 Pins | 667-061    | 550.00       |
|                 |         | 667-029    | 450.00       |

### IC-51 Series

#### SQFP, PQFP, TQFP 系列

#### SQFP, PQFP, TQFP Series

- \* High reliability, durability and temperature range
- \* Custom made also available for high pin count and fine-pitch IC packages



| MODEL             | 64 Pins  | STOCK CODE | PRICE (HK\$) |
|-------------------|----------|------------|--------------|
| IC51-0644-807     | 64 Pins  | 667-098    | 515.00       |
| IC51-0644-820-4   | 64 Pins  | 667-083    | 490.00       |
| IC51-0724-651     | 72 Pins  | 667-124    | 450.00       |
| IC51-0804-808     | 80 Pins  | 667-105    | 450.00       |
| IC51-0804-808-2   | 80 Pins  | 667-100    | 450.00       |
| IC51-0804-819-1   | 80 Pins  | 667-086    | 420.00       |
| IC51-0804-819-2   | 80 Pins  | 667-026    | 430.00       |
| IC51-0804-956-2   | 80 Pins  | 667-024    | 550.00       |
| IC51-1004-809     | 100 Pins | 667-060    | 540.00       |
| IC51-1004-814-2   | 100 Pins | 667-045    | 525.00       |
| IC51-1004-958-2   | 100 Pins | 667-111    | 510.00       |
| IC51-1204-1497    | 120 Pins | 667-058    | 680.00       |
| IC51-1497-KS11144 | 120 Pins | 667-059    | 1,100.00     |
| IC51-1284-1433-1  | 128 Pins | 667-068    | 1,150.00     |
| IC51-1284-844-1   | 128 Pins | 667-013    | 550.00       |
| IC51-1284-976-1   | 128 Pins | 667-014    | 825.00       |
| IC51-1444-1014    | 144 Pins | 667-030    | 1,300.00     |
| IC51-1444-1354    | 144 Pins | 667-099    | 2,000.00     |
| IC51-1604-845-1   | 160 Pins | 667-046    | 950.00       |
| IC51-1604-845-4   | 160 Pins | 667-015    | 975.00       |
| IC51-1764-1505    | 176 Pins | 667-101    | 800.00       |
| IC51-2084-1052-8  | 208 Pins | 667-017    | 1,295.00     |
| IC51-NP210-320    | 320 Pins | 667-048    | 80.00        |

### IC51 Series

#### QFP 系列

#### QFP Series

- \* High reliability, durability and temperature range Custom made also available for high pin count and fine-pitch IC packages



| MODEL            | 44 Pins  | STOCK CODE | PRICE (HK\$) |
|------------------|----------|------------|--------------|
| IC51-0444-1195-3 | 44 Pins  | 667-082    | 600.00       |
| IC51-0444-615    | 44 Pins  | 667-056    | 420.00       |
| IC51-0444-621    | 44 Pins  | 667-057    | 420.00       |
| IC51-0444-798    | 44 Pins  | 667-063    | 430.00       |
| IC51-0444-825    | 44 Pins  | 667-004    | 430.00       |
| IC51-0444-954-1  | 44 Pins  | 667-027    | 350.00       |
| IC51-0484-081    | 48 Pins  | 667-122    | 415.00       |
| IC51-0604-468    | 60 Pins  | 667-064    | 520.00       |
| IC51-0644-692    | 64 Pins  | 667-020    | 420.00       |
| IC51-0804-1200   | 80 Pins  | 667-022    | 468.00       |
| IC51-0804-711    | 80 Pins  | 667-035    | 580.00       |
| IC51-0804-795    | 80 Pins  | 667-019    | 550.00       |
| IC51-0804-819-6  | 80 Pins  | 667-120    | 450.00       |
| IC51-0804-956    | 80 Pins  | 667-018    | 550.00       |
| IC51-1004-395    | 100 Pins | 667-005    | 525.00       |
| IC51-1604-845    | 160 Pins | 667-031    | 950.00       |